U. S. ARMY





NOTES

1. HORIZONTAL CONTROL IS ALASKA STATE PLANE, ZONE 4, NAD83 IN U.S. SURVEY FEET HOLDING USACE SBC "N END 1978" AS N 2,646,652.19, E 1,660,582.43 AND USACE SBC "S END 1978" AS N 2,644,298.25, E 1,659,725.47.
2. VERTICAL CONTROL IS MEAN-LOWER-LOW-WATER (MLLW = 0.0') IN U.S. SURVEY FEET BASED ON NOAA/NOS TIDAL DATUM "9455920 ANCHORAGE, KNIK ARM, COOK INLET, ALASKA", PUBLISHED 04/21/2003, HOLDING USCGS SBC "B 75 1964" AS 36.82' AND NOAA/NOS TIDAL DATUM "9455912 FIRE ISLAND, ALASKA", PUBLISHED 05/21/2004, HOLDING NOS SBC "BM 13 1974" AS 28.41'. (SEE NOTE 4)
3. THIS SURVEY WAS CONDUCTED AUGUST 17–20, 2007. SOUNDINGS WERE COLLECTED USING A RESON SEABAT 8101 MULTIBEAM ECHOSOUNDER SYSTEM WITH A 240kHZ, 150 DEGREE SWATH-WIDTH TRANSDUCER (101 – 1.5 DEGREE BEAMS). POSITIONING, VESSEL ATTITUDE, HEADING AND TIDES WERE PROVIDED IN REAL-TIME USING AN APPLANIX POS M/V INERTIAL ATTITUDE AND POSITIONING SYSTEM OPERATING ON KINEMATIC GPS CORRECTIONS BROADCAST FROM A TRIMBLE 7400MSI RTK BASE RECEIVER SET AT "TERRA-9 2005", LOCATED ATOP THE PORT OF ANCHORAGE ADMINISTRATION BUILDING. SOUND VELOCITY WAS MEASURED AND APPLIED USING AN ODOM DIGI-BAR PRO SOUND VELOCITY PROFILER DEPLOYED DURING THE SURVEY. REAL-TIME-KINEMATIC HEIGHT VALUES WERE CALIBRATED TO DIRECT MANUAL TIDE OBSERVATIONS HOLDING USCGS SBC "B 75 1964" LOCATED AT NOAA/NOS TIDE STATION "9455920" AT THE PORT OF ANCHORAGE (SEE NOTE 4). SURVEY LINE NAVIGATION AND DATA COLLECTION WERE CONDUCTED USING QPS QINSY (V7.5) INTEGRATED SOFTWARE. DATA PROCESSING WAS PERFORMED USING A COMBINATION OF QPS QINSY AND CARIS HIPS (V6.1) SOFTWARE.
4. THE SURVEY AND THE PRELIMINARY PROCESSED DATASET WAS BASED ON RTK MLLW TIDE DATUM AT THE PORT OF ANCHORAGE AS NOTED ABOVE. THE FINAL DATASET WAS ADJUSTED TO REFLECT THE DIFFERENCE IN TIDE DATUM VALUES AT THE PORT OF ANCHORAGE (NOAA/NOS 9455920) AND THE TIDE DATUM VALUES AT FIRE ISLAND (NOAA/NOS 9455912). THIS "TILTED PLANE" ADJUSTMENT WAS PERFORMED TO PROVIDE A UNIFORM MLLW BASED APPROACH FROM THE WEST END OF THE COOK INLET NAVIGATION CHANNEL INTO THE PORT OF ANCHORAGE. THE ADJUSTMENT IS BASED ON OBSERVED RTK HEIGHT VALUES MEASURED AT BOTH NOAA/NOS TIDE STATIONS LISTED ABOVE. THE OBSERVED RTK DIFFERENCE HOLDS THE PORT OF ANCHORAGE AT 0.0' AND FIRE ISLAND AT −3.73'. THE ADJUSTMENT WAS PERFORMED USING A PROPRIETARY "LINEAR INTERPOLATION VERTICAL ADJUSTMENT ROUTINE" RAISING ALL SOUNDINGS PROPORTIONATELY ALONG THE DISTANCE BETWEEN THE TIDAL BENCH MARKS UTILIZED TO DEFINE THE VERTICAL DATUM. THE ADJUSTMENT AT THE PORT OF ANCHORAGE IS 0.0' EXTENDING TO AN ADJUSTMENT OF +3.73' AT FIRE ISLAND (SEE DIAGRAM SHEET 1).
5. SOUNDINGS ARE IN U.S. SURVEY FEET AND ARE MINUS UNLESS NOTED OTHERWISE.
6. THIS DRAWING IS INDICATIVE OF CONDITIONS AT THE TIME OF SURVEY.
7. NO NEW HORIZONTAL OR VERTICAL CONTROL MONUMENTS WERE ESTABLISHED DURING THIS SURVEY.

SURVEYOR'S CERTIFICATE

I HEREBY CERTIFY THAT I AM PROPERLY REGISTERED AND LICENSED TO PRACTICE LAND SURVEYING IN THE STATE OF ALASKA AND THAT THIS PLAT REPRESENTS A HYDROGRAPHIC SURVEY MADE BY ME OR UNDER MY DIRECT SUPERVISION. THE ELEVATIONS SHOWN HEREON DEPICT THE DEPTHS AS SURVEYED AUGUST 17–20, 2007 TO THE BEST OF MY KNOWLEDGE AND BELIEF.

STATE OF ALASKA 49TH KARL D. WOODS No.10950 REGISTERED PROFESSIONAL LAND SURVEYOR

KARL D. WOODS, P.L.S.
REGISTRATION NO. LS 10950

12.6.07
DATE

COOK INLET NAVIGATION CHANNEL COORDINATES

CHANNEL CENTERLINE

COR.	NORTHING	EASTING	STATION	DESCRIPTION
CL1	2,626,865.50	1,613,018.09	0+00	CENTERLINE WORONZOF RANGELINE
CL2	2,628,048.21	1,619,409.58	65+00	WORONZOF/FIRE ISLAND RANGELINE INTERSECTION
CL3	2,639,188.27	1,640,441.44	303+00	FIRE ISLAND/TRANSITION TO POA APPROACH
CL4	2,641,712.17	1,650,169.36	403+50	POA APPROACH
CL5	2,644,429.31	1,655,293.53	461+50	CENTERLINE POA APPROACH

CHANNEL LIMITS

COR.	NORTHING	EASTING	STATION	COR.	NORTHING	EASTING	STATION
NC1	2,627,365.51	1,612,925.56		NC6	2,638,711.03	1,640,626.80	
NC2	2,628,534.04	1,619,240.43		NC7	2,642,189.38	1,649,983.88	
NC3	2,639,665.52	1,640,256.07		NC8	2,644,878.56	1,655,055.31	
NC4	2,626,365.49	1,613,110.61		NC9	2,641,234.95	1,650,354.84	
NC5	2,627,562.38	1,619,578.73		NC10	2,643,980.06	1,655,531.75	

SURVEY LIMITS

CORNER	NORTHING	EASTING	CORNER	NORTHING	EASTING
SL1	2,628,340.46	1,612,745.15	SL6	2,637,780.48	1,640,988.24
SL2	2,629,481.34	1,618,910.61	SL7	2,643,119.87	1,649,622.22
SL3	2,641,596.07	1,639,894.63	SL8	2,645,754.53	1,654,590.82
SL4	2,625,390.54	1,613,291.02	SL9	2,640,304.46	1,650,716.50
SL5	2,626,615.08	1,619,908.55	SL10	2,643,104.09	1,655,996.24

CONTROL COORDINATES

STATION	NORTHING	EASTING	ELEVATION	DESCRIPTION
N END 1978	2,646,652.19	1,660,582.43	41.39	USACE SBC
S END 1978	2,644,295.69	1,659,728.19	40.37	USACE SBC
TERRA-9 2005	2,644,992.51	1,660,164.06	80.38	PORT OFFICE ANT. MOUNT
PORT 1989	2,639,936.64	1,656,922.51	39.93	USACE SAC
EQ-1	2,629,995.41	1,643,787.75	–	–
VAN DUSEN GPS 1986	2,621,198.82	1,648,753.69	–	NGS SBC
AWWU 1994	2,629,310.76	1,635,837.68	–	3" ALCAP
NOAA/NOS TIDAL BENCH MARKS AT THE PORT OF ANCHORAGE 9455920				
TIDAL 16 1966	2,644,293	1,659,727	40.53	USCGS BENCH MARK SBC
B 75 1964	2,644,598	1,660,095	36.82	USCGS BENCH MARK SBC
NOAA/NOS TIDAL BENCH MARKS AT FIRE ISLAND 9455912				
BM 13 1974	2,620,685	1,605,138	28.41	NOS TIDAL BENCH MARK SBC
RIFE 1960	2,620,520	1,604,180	29.99	USCGS TRI-STA SBC

REAL-TIME-KINEMATIC GPS TIDES
DATUM ADJUSTMENT BASIS

CONTRACT NO. W911KB-07-D-0005
CONTRACTOR TERRA SURVEYS, LLC
CITY PALMER STATE ALASKA

ALASKA DISTRICT
CORPS OF ENGINEERS
ANCHORAGE, ALASKA

SURVEYED: SC/SM/CM
DRAWN: S. LEATHAM
CHECKED: KDW
SUBMITTED:

ANCHORAGE, ALASKA
COOK INLET NAVIGATION CHANNEL
PROJECT CONDITION SURVEY
AUGUST 17–20, 2007

RECOMMENDED: PROJECT MANAGER
APPROVED: CHIEF OPERATIONS-READINESS BRANCH
DATE:

SURVEY NO. 2477-07

SCALE: 1" = 3000'

SHEET 1 OF 11



C.I.N.C. – DISPOSAL SITE LIMITS					
CORNER	NORTHING	EASTING	CORNER	NORTHING	EASTING
D1	2,626,323.49	1,614,048.61	D3	2,624,354.99	1,614,048.61
D2	2,626,323.49	1,616,673.28	D4	2,624,354.99	1,616,673.28



NOTES

1. HORIZONTAL CONTROL IS ALASKA STATE PLANE, ZONE 4, NAD83 IN U.S. SURVEY FEET HOLDING USACE SBC "N END 1978" AS N 2,646,652.19, E 1,660,582.43 AND USACE SBC "S END 1978" AS N 2,644,298.25, E 1,659,725.47.
2. VERTICAL CONTROL IS MEAN-LOWER-LOW-WATER (MLLW = 0.0') IN U.S. SURVEY FEET BASED ON NOAA/NOS TIDAL DATUM "9455920 ANCHORAGE, KNIK ARM, COOK INLET, ALASKA", PUBLISHED 04/21/2003, HOLDING USCGS SBC "B 75 1964" AS 36.82' AND NOAA/NOS TIDAL DATUM "9455912 FIRE ISLAND, ALASKA", PUBLISHED 05/21/2004, HOLDING NOS SBC "BM 13 1974" AS 28.41'. (SEE NOTE 4)
3. THIS SURVEY WAS CONDUCTED AUGUST 17–20, 2007. SOUNDINGS WERE COLLECTED USING A RESON SEABAT 8101 MULTIBEAM ECHOSOUNDER SYSTEM WITH A 240kHZ, 150 DEGREE SWATH-WIDTH TRANSDUCER (101 – 1.5 DEGREE BEAMS). POSITIONING, VESSEL ATTITUDE, HEADING AND TIDES WERE PROVIDED IN REAL-TIME USING AN APPLANIX POS M/V INERTIAL ATTITUDE AND POSITIONING SYSTEM OPERATING ON KINEMATIC GPS CORRECTIONS BROADCAST FROM A TRIMBLE 7400MSI RTK BASE RECEIVER SET AT "TERRA-9 2005", LOCATED ATOP THE PORT OF ANCHORAGE ADMINISTRATION BUILDING. SOUND VELOCITY WAS MEASURED AND APPLIED USING AN ODOM DIGI-BAR PRO SOUND VELOCITY PROFILER DEPLOYED DURING THE SURVEY. REAL-TIME-KINEMATIC HEIGHT VALUES WERE CALIBRATED TO DIRECT MANUAL TIDE OBSERVATIONS HOLDING USCGS SBC "B 75 1964" LOCATED AT NOAA/NOS TIDE STATION "9455920" AT THE PORT OF ANCHORAGE (SEE NOTE 4). SURVEY LINE NAVIGATION AND DATA COLLECTION WERE CONDUCTED USING QPS QINSY (V7.5) INTEGRATED SOFTWARE. DATA PROCESSING WAS PERFORMED USING A COMBINATION OF QPS QINSY AND CARIS HIPS (V6.1) SOFTWARE.
4. THE SURVEY AND THE PRELIMINARY PROCESSED DATASET WAS BASED ON RTK MLLW TIDE DATUM AT THE PORT OF ANCHORAGE AS NOTED ABOVE. THE FINAL DATASET WAS ADJUSTED TO REFLECT THE DIFFERENCE IN TIDE DATUM VALUES AT THE PORT OF ANCHORAGE (NOAA/NOS 9455920) AND THE TIDE DATUM VALUES AT FIRE ISLAND (NOAA/NOS 9455912). THIS "TILTED PLANE" ADJUSTMENT WAS PERFORMED TO PROVIDE A UNIFORM MLLW BASED APPROACH FROM THE WEST END OF THE COOK INLET NAVIGATION CHANNEL INTO THE PORT OF ANCHORAGE. THE ADJUSTMENT IS BASED ON OBSERVED RTK HEIGHT VALUES MEASURED AT BOTH NOAA/NOS TIDE STATIONS LISTED ABOVE. THE OBSERVED RTK DIFFERENCE HOLDS THE PORT OF ANCHORAGE AT 0.0' AND FIRE ISLAND AT –3.73'. THE ADJUSTMENT WAS PERFORMED USING A PROPRIETARY "LINEAR INTERPOLATION VERTICAL ADJUSTMENT ROUTINE" RAISING ALL SOUNDINGS PROPORTIONATELY ALONG THE DISTANCE BETWEEN THE TIDAL BENCH MARKS UTILIZED TO DEFINE THE VERTICAL DATUM. THE ADJUSTMENT AT THE PORT OF ANCHORAGE IS 0.0' EXTENDING TO AN ADJUSTMENT OF +3.73' AT FIRE ISLAND (SEE DIAGRAM SHEET 1).
5. SOUNDINGS ARE IN U.S. SURVEY FEET AND ARE MINUS UNLESS NOTED OTHERWISE.
6. THIS DRAWING IS INDICATIVE OF CONDITIONS AT THE TIME OF SURVEY.
7. NO NEW HORIZONTAL OR VERTICAL CONTROL MONUMENTS WERE ESTABLISHED DURING THIS SURVEY.

COOK INLET NAVIGATION CHANNEL COORDINATES				
CHANNEL CENTERLINE				
COR.	NORTHING	EASTING	STATION	DESCRIPTION
CL1	2,626,865.50	1,613,018.09	0+00	CENTERLINE WORONZOF RANGELINE
CL2	2,628,048.21	1,619,409.58	65+00	WORONZOF/FIRE ISLAND RANGELINE INTERSECTION
CL3	2,639,188.27	1,640,441.44	303+00	FIRE ISLAND/TRANSITION TO POA APPROACH
CL4	2,641,712.17	1,650,169.36	403+50	POA APPROACH
CL5	2,644,429.31	1,655,293.53	461+50	CENTERLINE POA APPROACH

CHANNEL LIMITS							
COR.	NORTHING	EASTING	STATION	COR.	NORTHING	EASTING	STATION
NC1	2,627,365.51	1,612,925.56		NC6	2,638,711.03	1,640,626.80	
NC2	2,628,534.04	1,619,240.43		NC7	2,642,189.38	1,649,983.88	
NC3	2,639,665.52	1,640,256.07		NC8	2,644,878.56	1,655,055.31	
NC4	2,626,365.49	1,613,110.61		NC9	2,641,234.95	1,650,354.84	
NC5	2,627,562.38	1,619,578.73		NC10	2,643,980.06	1,655,531.75	

SURVEY LIMITS					
CORNER	NORTHING	EASTING	CORNER	NORTHING	EASTING
SL1	2,628,340.46	1,612,745.15	SL6	2,637,780.48	1,640,988.24
SL2	2,629,481.34	1,618,910.61	SL7	2,643,119.87	1,649,622.22
SL3	2,641,596.07	1,639,894.63	SL8	2,645,754.53	1,654,590.82
SL4	2,625,390.54	1,613,291.02	SL9	2,640,304.46	1,650,716.50
SL5	2,626,615.08	1,619,908.55	SL10	2,643,104.09	1,655,996.24

⚠ CONTROL COORDINATES ⚠				
STATION	NORTHING	EASTING	ELEVATION	DESCRIPTION
N END 1978	2,646,652.19	1,660,582.43	41.39	USACE SBC
S END 1978	2,644,295.69	1,659,728.19	40.37	USACE SBC
TERRA-9 2005	2,644,992.51	1,660,164.06	80.38	PORT OFFICE ANT. MOUNT
PORT 1989	2,639,936.64	1,656,922.51	39.93	USACE SAC
EQ-1	2,629,995.41	1,643,787.75	–	–
VAN DUSEN GPS 1986	2,621,198.82	1,648,753.69	–	NGS SBC
AWWU 1994	2,629,310.76	1,635,837.68	–	3" ALCAP
NOAA/NOS TIDAL BENCH MARKS AT THE PORT OF ANCHORAGE 9455920				
TIDAL 16 1986	2,644,293	1,659,727	40.53	USCGS BENCH MARK SBC
B 75 1954	2,644,598	1,660,095	36.82	USCGS BENCH MARK SBC
NOAA/NOS TIDAL BENCH MARKS AT FIRE ISLAND 9455912				
BM 13 1974	2,620,685	1,605,138	28.41	NOS TIDAL BENCH MARK SBC
RIFE 1960	2,620,520	1,604,180	29.99	USCGS TRI-STA SBC

CONTRACT NO. W911KB-07-D-0005

CONTRACTOR TERRA SURVEYS, LLC

CITY PALMER STATE ALASKA

ALASKA DISTRICT
CORPS OF ENGINEERS
ANCHORAGE, ALASKA

SURVEYED: SC/SM/CM	ANCHORAGE, ALASKA
DRAWN: S. LEATHAM	COOK INLET NAVIGATION CHANNEL
CHECKED: KDW	PROJECT CONDITION SURVEY
SUBMITTED:	AUGUST 17–20, 2007

RECOMMENDED: PROJECT MANAGER

APPROVED: CHIEF OPERATIONS-READINESS BRANCH

DATE:

SURVEY NO. 2477-07

SCALE: 1" = 200'

SHEET 2 OF 11





NOTES

1. HORIZONTAL CONTROL IS ALASKA STATE PLANE, ZONE 4, NAD83 IN U.S. SURVEY FEET HOLDING USACE SBC "N END 1978" AS N 2,646,652.19, E 1,660,582.43 AND USACE SBC "S END 1978" AS N 2,644,298.25, E 1,659,725.47.
2. VERTICAL CONTROL IS MEAN-LOWER-LOW-WATER (MLLW = 0.0') IN U.S. SURVEY FEET BASED ON NOAA/NOS TIDAL DATUM "9455920 ANCHORAGE, KNIK ARM, COOK INLET, ALASKA", PUBLISHED 04/21/2003, HOLDING USCGS SBC "B 75 1964" AS 36.82' AND NOAA/NOS TIDAL DATUM "9455912 FIRE ISLAND, ALASKA", PUBLISHED 05/21/2004, HOLDING NOS SBC "BM 13 1974" AS 28.41'. (SEE NOTE 4)
3. THIS SURVEY WAS CONDUCTED AUGUST 17–20, 2007. SOUNDINGS WERE COLLECTED USING A RESON SEABAT 8101 MULTIBEAM ECHOSOUNDER SYSTEM WITH A 240KHZ, 150 DEGREE SWATH-WIDTH TRANSDUCER (101 – 1.5 DEGREE BEAMS). POSITIONING, VESSEL ATTITUDE, HEADING AND TIDES WERE PROVIDED IN REAL-TIME USING AN APPLANIX POS M/V INERTIAL ATTITUDE AND POSITIONING SYSTEM OPERATING ON KINEMATIC GPS CORRECTIONS BROADCAST FROM A TRIMBLE 7400MSI RTK BASE RECEIVER SET AT "TERRA-9 2005", LOCATED ATOP THE PORT OF ANCHORAGE ADMINISTRATION BUILDING. SOUND VELOCITY WAS MEASURED AND APPLIED USING AN ODOM DIGI-BAR PRO SOUND VELOCITY PROFILER DEPLOYED DURING THE SURVEY. REAL-TIME-KINEMATIC HEIGHT VALUES WERE CALIBRATED TO DIRECT MANUAL TIDE OBSERVATIONS HOLDING USCGS SBC "B 75 1964" LOCATED AT NOAA/NOS TIDE STATION "9455920" AT THE PORT OF ANCHORAGE (SEE NOTE 4). SURVEY LINE NAVIGATION AND DATA COLLECTION WERE CONDUCTED USING QPS QINSY (V7.5) INTEGRATED SOFTWARE. DATA PROCESSING WAS PERFORMED USING A COMBINATION OF QPS QINSY AND CARIS HIPS (V6.1) SOFTWARE.
4. THE SURVEY AND THE PRELIMINARY PROCESSED DATASET WAS BASED ON RTK MLLW TIDE DATUM AT THE PORT OF ANCHORAGE AS NOTED ABOVE. THE FINAL DATASET WAS ADJUSTED TO REFLECT THE DIFFERENCE IN TIDE DATUM VALUES AT THE PORT OF ANCHORAGE (NOAA/NOS 9455920) AND THE TIDE DATUM VALUES AT FIRE ISLAND (NOAA/NOS 9455912). THIS "TILTED PLANE" ADJUSTMENT WAS PERFORMED TO PROVIDE A UNIFORM MLLW BASED APPROACH FROM THE WEST END OF THE COOK INLET NAVIGATION CHANNEL INTO THE PORT OF ANCHORAGE. THE ADJUSTMENT IS BASED ON OBSERVED RTK HEIGHT VALUES MEASURED AT BOTH NOAA/NOS TIDE STATIONS LISTED ABOVE. THE OBSERVED RTK DIFFERENCE HOLDS THE PORT OF ANCHORAGE AT 0.0' AND FIRE ISLAND AT −3.73'. THE ADJUSTMENT WAS PERFORMED USING A PROPRIETARY "LINEAR INTERPOLATION VERTICAL ADJUSTMENT ROUTINE" RAISING ALL SOUNDINGS PROPORTIONATELY ALONG THE DISTANCE BETWEEN THE TIDAL BENCH MARKS UTILIZED TO DEFINE THE VERTICAL DATUM. THE ADJUSTMENT AT THE PORT OF ANCHORAGE IS 0.0' EXTENDING TO AN ADJUSTMENT OF +3.73' AT FIRE ISLAND (SEE DIAGRAM SHEET 1).
5. SOUNDINGS ARE IN U.S. SURVEY FEET AND ARE MINUS UNLESS NOTED OTHERWISE.
6. THIS DRAWING IS INDICATIVE OF CONDITIONS AT THE TIME OF SURVEY.
7. NO NEW HORIZONTAL OR VERTICAL CONTROL MONUMENTS WERE ESTABLISHED DURING THIS SURVEY.

COOK INLET NAVIGATION CHANNEL COORDINATES

CHANNEL CENTERLINE

COR.	NORTHING	EASTING	STATION	DESCRIPTION
CL1	2,626,865.50	1,613,018.09	0+00	CENTERLINE WORONZOF RANGELINE
CL2	2,628,048.21	1,619,409.58	65+00	WORONZOF/FIRE ISLAND RANGELINE INTERSECTION
CL3	2,639,188.27	1,640,441.44	303+00	FIRE ISLAND/TRANSITION TO POA APPROACH
CL4	2,641,712.17	1,650,169.36	403+50	POA APPROACH
CL5	2,644,429.31	1,655,293.53	461+50	CENTERLINE POA APPROACH

CHANNEL LIMITS

COR.	NORTHING	EASTING	STATION	COR.	NORTHING	EASTING	STATION
NC1	2,627,365.51	1,612,925.56		NC6	2,638,711.03	1,640,626.80	
NC2	2,628,534.04	1,619,240.43		NC7	2,642,189.38	1,649,983.88	
NC3	2,639,665.52	1,640,256.07		NC8	2,644,878.56	1,655,055.31	
NC4	2,626,365.49	1,613,110.61		NC9	2,641,234.95	1,650,354.84	
NC5	2,627,562.38	1,619,578.73		NC10	2,643,980.06	1,655,531.75	

SURVEY LIMITS

CORNER	NORTHING	EASTING	CORNER	NORTHING	EASTING
SL1	2,628,340.46	1,612,745.15	SL6	2,637,780.48	1,640,988.24
SL2	2,629,481.34	1,618,910.61	SL7	2,643,119.87	1,649,622.22
SL3	2,641,596.07	1,639,894.63	SL8	2,645,754.53	1,654,590.82
SL4	2,625,390.54	1,613,291.02	SL9	2,640,304.46	1,650,716.50
SL5	2,626,615.08	1,619,908.55	SL10	2,643,104.09	1,655,996.24

⚠ CONTROL COORDINATES ⚠

STATION	NORTHING	EASTING	ELEVATION	DESCRIPTION
N END 1978	2,646,652.19	1,660,582.43	41.39	USACE SBC
S END 1978	2,644,295.69	1,659,728.19	40.37	USACE SBC
TERRA-9 2005	2,644,992.51	1,660,164.06	80.38	PORT OFFICE ANT. MOUNT
PORT 1989	2,639,936.64	1,656,922.51	39.93	USACE SAC
EQ-1	2,629,995.41	1,643,787.75	--	--
VAN DUSEN GPS 1986	2,621,198.82	1,648,753.69	--	NGS SBC
AWWU 1994	2,629,310.76	1,635,837.68	--	3" ALCAP
NOAA/NOS TIDAL BENCH MARKS AT THE PORT OF ANCHORAGE 9455920				
TIDAL 16 1966	2,644,293	1,659,727	40.53	USCGS BENCH MARK SBC
B 75 1964	2,644,598	1,660,095	36.82	USCGS BENCH MARK SBC
NOAA/NOS TIDAL BENCH MARKS AT FIRE ISLAND 9455912				
BM 13 1974	2,620,685	1,605,138	28.41	NOS TIDAL BENCH MARK SBC
RIFE 1960	2,620,520	1,604,180	29.99	USCGS TRI-STA SBC

CONTRACT NO. W911KB-07-D-0005
CONTRACTOR TERRA SURVEYS, LLC
CITY PALMER STATE ALASKA

ALASKA DISTRICT
CORPS OF ENGINEERS
ANCHORAGE, ALASKA

SURVEYED: SC/SM/CM	ANCHORAGE, ALASKA
DRAWN: S. LEATHAM	COOK INLET NAVIGATION CHANNEL
CHECKED: KDW	PROJECT CONDITION SURVEY
SUBMITTED:	AUGUST 17–20, 2007

RECOMMENDED: PROJECT MANAGER
APPROVED: CHIEF OPERATIONS-READINESS BRANCH
DATE:

SURVEY NO. 2477-07

SCALE: 1" = 200'

SHEET 3 OF 11





NOTES

1. HORIZONTAL CONTROL IS ALASKA STATE PLANE, ZONE 4, NAD83 IN U.S. SURVEY FEET HOLDING USACE SBC "N END 1978" AS N 2,646,652.19, E 1,660,582.43 AND USACE SBC "S END 1978" AS N 2,644,295.25, E 1,659,725.47.
2. VERTICAL CONTROL IS MEAN–LOWER–LOW–WATER (MLLW = 0.0') IN U.S. SURVEY FEET BASED ON NOAA/NOS TIDAL DATUM "9455920 ANCHORAGE, KNIK ARM, COOK INLET, ALASKA", PUBLISHED 04/21/2003, HOLDING USCGS SBC "B 75 1964" AS 36.82' AND NOAA/NOS TIDAL DATUM "9455912 FIRE ISLAND, ALASKA", PUBLISHED 05/21/2004, HOLDING NOS SBC "BM 13 1974" AS 28.41'. (SEE NOTE 4)
3. THIS SURVEY WAS CONDUCTED AUGUST 17–20, 2007. SOUNDINGS WERE COLLECTED USING A RESON SEABAT 8101 MULTIBEAM ECHOSOUNDER SYSTEM WITH A 240KHZ, 150 DEGREE SWATH–WIDTH TRANSDUCER (101 – 1.5 DEGREE BEAMS). POSITIONING, VESSEL ATTITUDE, HEADING AND TIDES WERE PROVIDED IN REAL–TIME USING AN APPLANIX POS M/V INERTIAL ATTITUDE AND POSITIONING SYSTEM OPERATING ON KINEMATIC GPS CORRECTIONS BROADCAST FROM A TRIMBLE 7400MSI RTK BASE RECEIVER SET AT "TERRA–9 2005", LOCATED ATOP THE PORT OF ANCHORAGE ADMINISTRATION BUILDING. SOUND VELOCITY WAS MEASURED AND APPLIED USING AN ODOM DIGI–BAR PRO SOUND VELOCITY PROFILER DEPLOYED DURING THE SURVEY. REAL–TIME–KINEMATIC HEIGHT VALUES WERE CALIBRATED TO DIRECT MANUAL TIDE OBSERVATIONS HOLDING USCGS SBC "B 75 1964" LOCATED AT NOAA/NOS TIDE STATION "9455920" AT THE PORT OF ANCHORAGE (SEE NOTE 4). SURVEY LINE NAVIGATION AND DATA COLLECTION WERE CONDUCTED USING QPS QINSY (V7.5) INTEGRATED SOFTWARE. DATA PROCESSING WAS PERFORMED USING A COMBINATION OF QPS QINSY AND CARIS HIPS (V6.1) SOFTWARE.
4. THE SURVEY AND THE PRELIMINARY PROCESSED DATASET WAS BASED ON RTK MLLW TIDE DATUM AT THE PORT OF ANCHORAGE AS NOTED ABOVE. THE FINAL DATASET WAS ADJUSTED TO REFLECT THE DIFFERENCE IN TIDE DATUM VALUES AT THE PORT OF ANCHORAGE (NOAA/NOS 9455920) AND THE TIDE DATUM VALUES AT FIRE ISLAND (NOAA/NOS 9455912). THIS "TILTED PLANE" ADJUSTMENT WAS PERFORMED TO PROVIDE A UNIFORM MLLW BASED APPROACH FROM THE WEST END OF THE COOK INLET NAVIGATION CHANNEL INTO THE PORT OF ANCHORAGE. THE ADJUSTMENT IS BASED ON OBSERVED RTK HEIGHT VALUES MEASURED AT BOTH NOAA/NOS TIDE STATIONS LISTED ABOVE. THE OBSERVED RTK DIFFERENCE HOLDS THE PORT OF ANCHORAGE AT 0.0' AND FIRE ISLAND AT –3.73'. THE ADJUSTMENT WAS PERFORMED USING A PROPRIETARY "LINEAR INTERPOLATION VERTICAL ADJUSTMENT ROUTINE" RAISING ALL SOUNDINGS PROPORTIONATELY ALONG THE DISTANCE BETWEEN THE TIDAL BENCH MARKS UTILIZED TO DEFINE THE VERTICAL DATUM. THE ADJUSTMENT AT THE PORT OF ANCHORAGE IS 0.0' EXTENDING TO AN ADJUSTMENT OF +3.73' AT FIRE ISLAND (SEE DIAGRAM SHEET 1).
5. SOUNDINGS ARE IN U.S. SURVEY FEET AND ARE MINUS UNLESS NOTED OTHERWISE.
6. THIS DRAWING IS INDICATIVE OF CONDITIONS AT THE TIME OF SURVEY.
7. NO NEW HORIZONTAL OR VERTICAL CONTROL MONUMENTS WERE ESTABLISHED DURING THIS SURVEY.

COOK INLET NAVIGATION CHANNEL COORDINATES

CHANNEL CENTERLINE

COR.	NORTHING	EASTING	STATION	DESCRIPTION
CL1	2,626,865.50	1,613,018.09	0+00	CENTERLINE WORONZOF RANGELINE
CL2	2,628,048.21	1,619,409.58	65+00	WORONZOF/FIRE ISLAND RANGELINE INTERSECTION
CL3	2,639,188.27	1,640,441.44	303+00	FIRE ISLAND/TRANSITION TO POA APPROACH
CL4	2,641,712.17	1,650,169.36	403+50	POA APPROACH
CL5	2,644,429.31	1,655,293.53	461+50	CENTERLINE POA APPROACH

CHANNEL LIMITS

COR.	NORTHING	EASTING	STATION	COR.	NORTHING	EASTING	STATION
NC1	2,627,365.51	1,612,925.56		NC6	2,638,711.03	1,640,626.80	
NC2	2,628,534.04	1,619,240.43		NC7	2,642,189.38	1,649,983.88	
NC3	2,639,665.52	1,640,256.07		NC8	2,644,878.56	1,655,055.31	
NC4	2,626,365.49	1,613,110.61		NC9	2,641,234.95	1,650,354.84	
NC5	2,627,562.38	1,619,578.73		NC10	2,643,980.06	1,655,531.75	

SURVEY LIMITS

CORNER	NORTHING	EASTING	CORNER	NORTHING	EASTING
SL1	2,628,340.46	1,612,745.15	SL6	2,637,780.48	1,640,988.24
SL2	2,629,481.34	1,618,910.61	SL7	2,643,119.87	1,649,622.22
SL3	2,641,596.07	1,639,894.63	SL8	2,645,754.53	1,654,590.82
SL4	2,625,390.54	1,613,291.02	SL9	2,640,304.46	1,650,716.50
SL5	2,626,615.08	1,619,908.55	SL10	2,643,104.09	1,655,996.24

△ CONTROL COORDINATES △

STATION	NORTHING	EASTING	ELEVATION	DESCRIPTION
N END 1978	2,646,652.19	1,660,582.43	41.39	USACE SBC
S END 1978	2,644,295.69	1,659,728.19	40.37	USACE SBC
TERRA–9 2005	2,644,992.51	1,660,164.06	80.38	PORT OFFICE ANT. MOUNT
PORT 1989	2,639,936.64	1,656,922.51	39.93	USACE SAC
EQ–1	2,629,995.41	1,643,787.75	–	–
VAN DUSEN GPS 1986	2,621,198.82	1,648,753.69	–	NGS SBC
AWWU 1994	2,629,310.76	1,635,837.68	–	3" ALCAP
NOAA/NOS TIDAL BENCH MARKS AT THE PORT OF ANCHORAGE 9455920				
TIDAL 16 1966	2,644,293	1,659,727	40.53	USCGS BENCH MARK SBC
B 75 1964	2,644,598	1,660,095	36.82	USCGS BENCH MARK SBC
NOAA/NOS TIDAL BENCH MARKS AT FIRE ISLAND 9455912				
BM 13 1974	2,620,685	1,605,138	28.41	NOS TIDAL BENCH MARK SBC
RIFE 1960	2,620,520	1,604,180	29.99	USCGS TRI–STA SBC

CONTRACT NO. W911KB–07–D–0005
CONTRACTOR TERRA SURVEYS, LLC
CITY PALMER STATE ALASKA

ALASKA DISTRICT
CORPS OF ENGINEERS
ANCHORAGE, ALASKA

SURVEYED: SC/SM/CM
DRAWN: S. LEATHAM
CHECKED: KDW
SUBMITTED:

ANCHORAGE, ALASKA
COOK INLET NAVIGATION CHANNEL
PROJECT CONDITION SURVEY
AUGUST 17–20, 2007

RECOMMENDED: APPROVED: DATE:
PROJECT MANAGER CHIEF OPERATIONS–READINESS BRANCH

SURVEY NO. 2477–07

SCALE: 1" = 200'

SHEET 4 OF 11





NOTES

1. HORIZONTAL CONTROL IS ALASKA STATE PLANE, ZONE 4, NAD83 IN U.S. SURVEY FEET HOLDING USACE SBC "N END 1978" AS N 2,646,652.19, E 1,660,582.43 AND USACE SBC "S END 1978" AS N 2,644,295.25, E 1,659,725.47.
2. VERTICAL CONTROL IS MEAN–LOWER–LOW–WATER (MLLW = 0.0') IN U.S. SURVEY FEET BASED ON NOAA/NOS TIDAL DATUM "9455920 ANCHORAGE, KNIK ARM, COOK INLET, ALASKA", PUBLISHED 04/21/2003, HOLDING USCGS SBC "B 75 1964" AS 36.82' AND NOAA/NOS TIDAL DATUM "9455912 FIRE ISLAND, ALASKA", PUBLISHED 05/21/2004, HOLDING NOS SBC "BM 13 1974" AS 28.41'. (SEE NOTE 4)
3. THIS SURVEY WAS CONDUCTED AUGUST 17–20, 2007. SOUNDINGS WERE COLLECTED USING A RESON SEABAT 8101 MULTIBEAM ECHOSOUNDER SYSTEM WITH A 240kHZ, 150 DEGREE SWATH–WIDTH TRANSDUCER (101 – 1.5 DEGREE BEAMS). POSITIONING, VESSEL ATTITUDE, HEADING AND TIDES WERE PROVIDED IN REAL–TIME USING AN APPLANIX POS M/V INERTIAL ATTITUDE AND POSITIONING SYSTEM OPERATING ON KINEMATIC GPS CORRECTIONS BROADCAST FROM A TRIMBLE 7400MSI RTK BASE RECEIVER SET AT "TERRA–9 2005", LOCATED ATOP THE PORT OF ANCHORAGE ADMINISTRATION BUILDING. SOUND VELOCITY WAS MEASURED AND APPLIED USING AN ODOM DIGI–BAR PRO SOUND VELOCITY PROFILER DEPLOYED DURING THE SURVEY. REAL–TIME–KINEMATIC HEIGHT VALUES WERE CALIBRATED TO DIRECT MANUAL TIDE OBSERVATIONS HOLDING USCGS SBC "B 75 1964" LOCATED AT NOAA/NOS TIDE STATION "9455920" AT THE PORT OF ANCHORAGE (SEE NOTE 4). SURVEY LINE NAVIGATION AND DATA COLLECTION WERE CONDUCTED USING QPS QINSY (V7.5) INTEGRATED SOFTWARE. DATA PROCESSING WAS PERFORMED USING A COMBINATION OF QPS QINSY AND CARIS HIPS (V6.1) SOFTWARE.
4. THE SURVEY AND THE PRELIMINARY PROCESSED DATASET WAS BASED ON RTK MLLW TIDE DATUM AT THE PORT OF ANCHORAGE AS NOTED ABOVE. THE FINAL DATASET WAS ADJUSTED TO REFLECT THE DIFFERENCE IN TIDE DATUM VALUES AT THE PORT OF ANCHORAGE (NOAA/NOS 9455920) AND THE TIDE DATUM VALUES AT FIRE ISLAND (NOAA/NOS 9455912). THIS "TILTED PLANE" ADJUSTMENT WAS PERFORMED TO PROVIDE A UNIFORM MLLW BASED APPROACH FROM THE WEST END OF THE COOK INLET NAVIGATION CHANNEL INTO THE PORT OF ANCHORAGE. THE ADJUSTMENT IS BASED ON OBSERVED RTK HEIGHT VALUES MEASURED AT BOTH NOAA/NOS TIDE STATIONS LISTED ABOVE. THE OBSERVED RTK DIFFERENCE HOLDS THE PORT OF ANCHORAGE AT 0.0' AND FIRE ISLAND AT −3.73'. THE ADJUSTMENT WAS PERFORMED USING A PROPRIETARY "LINEAR INTERPOLATION VERTICAL ADJUSTMENT ROUTINE" RAISING ALL SOUNDINGS PROPORTIONATELY ALONG THE DISTANCE BETWEEN THE TIDAL BENCH MARKS UTILIZED TO DEFINE THE VERTICAL DATUM. THE ADJUSTMENT AT THE PORT OF ANCHORAGE IS 0.0' EXTENDING TO AN ADJUSTMENT OF +3.73' AT FIRE ISLAND (SEE DIAGRAM SHEET 1).
5. SOUNDINGS ARE IN U.S. SURVEY FEET AND ARE MINUS UNLESS NOTED OTHERWISE.
6. THIS DRAWING IS INDICATIVE OF CONDITIONS AT THE TIME OF SURVEY.
7. NO NEW HORIZONTAL OR VERTICAL CONTROL MONUMENTS WERE ESTABLISHED DURING THIS SURVEY.

COOK INLET NAVIGATION CHANNEL COORDINATES				
CHANNEL CENTERLINE				
COR.	NORTHING	EASTING	STATION	DESCRIPTION
CL1	2,626,865.50	1,613,018.09	0+00	CENTERLINE WORONZOF RANGELINE
CL2	2,628,048.21	1,619,409.58	65+00	WORONZOF/FIRE ISLAND RANGELINE INTERSECTION
CL3	2,639,188.27	1,640,441.44	303+00	FIRE ISLAND/TRANSITION TO POA APPROACH
CL4	2,641,712.17	1,650,169.36	403+50	POA APPROACH
CL5	2,644,429.31	1,655,293.53	461+50	CENTERLINE POA APPROACH

CHANNEL LIMITS							
COR.	NORTHING	EASTING	STATION	COR.	NORTHING	EASTING	STATION
NC1	2,627,365.51	1,612,925.56		NC6	2,638,711.03	1,640,626.80	
NC2	2,628,534.04	1,619,240.43		NC7	2,642,189.38	1,649,983.88	
NC3	2,639,665.52	1,640,256.07		NC8	2,644,878.56	1,655,055.31	
NC4	2,626,365.49	1,613,110.61		NC9	2,641,234.95	1,650,354.84	
NC5	2,627,562.38	1,619,578.73		NC10	2,643,980.06	1,655,531.75	

SURVEY LIMITS					
CORNER	NORTHING	EASTING	CORNER	NORTHING	EASTING
SL1	2,628,340.46	1,612,745.15	SL6	2,637,780.48	1,640,988.24
SL2	2,629,481.34	1,618,910.61	SL7	2,643,119.87	1,649,622.22
SL3	2,641,596.07	1,639,894.63	SL8	2,645,754.53	1,654,590.82
SL4	2,625,390.54	1,613,291.02	SL9	2,640,304.46	1,650,716.50
SL5	2,626,615.08	1,619,908.55	SL10	2,643,104.09	1,655,996.24

⚠ CONTROL COORDINATES ⚠				
STATION	NORTHING	EASTING	ELEVATION	DESCRIPTION
N END 1978	2,646,652.19	1,660,582.43	41.39	USACE SBC
S END 1978	2,644,295.69	1,659,728.19	40.37	USACE SBC
TERRA–9 2005	2,644,992.51	1,660,164.06	80.38	PORT OFFICE ANT. MOUNT
PORT 1989	2,639,936.64	1,656,922.51	39.93	USACE SAC
EQ–1	2,629,995.41	1,643,787.75	–	–
VAN DUSEN GPS 1986	2,621,198.82	1,648,753.69	–	NGS SBC
AWWU 1994	2,629,310.76	1,635,837.68	–	3" ALCAP
NOAA/NOS TIDAL BENCH MARKS AT THE PORT OF ANCHORAGE 9455920				
TIDAL 16 1966	2,644,293	1,659,727	40.53	USCGS BENCH MARK SBC
B 75 1964	2,644,598	1,660,095	36.82	USCGS BENCH MARK SBC
NOAA/NOS TIDAL BENCH MARKS AT FIRE ISLAND 9455912				
BM 13 1974	2,620,685	1,605,138	28.41	NOS TIDAL BENCH MARK SBC
RIFE 1960	2,620,520	1,604,180	29.99	USCGS TRI–STA SBC

CONTRACT NO. W911KB–07–D–0005
CONTRACTOR TERRA SURVEYS, LLC
CITY PALMER STATE ALASKA

ALASKA DISTRICT
CORPS OF ENGINEERS
ANCHORAGE, ALASKA

SURVEYED: SC/SM/CM
DRAWN: S. LEATHAM
CHECKED: KDW
SUBMITTED:

ANCHORAGE, ALASKA
COOK INLET NAVIGATION CHANNEL
PROJECT CONDITION SURVEY
AUGUST 17–20, 2007

RECOMMENDED: PROJECT MANAGER
APPROVED: CHIEF OPERATIONS–READINESS BRANCH
DATE:

SURVEY NO. 2477–07

SCALE: 1" = 200'

SHEET 5 OF 11





NOTES

1. HORIZONTAL CONTROL IS ALASKA STATE PLANE, ZONE 4, NAD83 IN U.S. SURVEY FEET HOLDING USACE SBC "N END 1978" AS N 2,646,652.19, E 1,660,582.43 AND USACE SBC "S END 1978" AS N 2,644,298.25, E 1,659,725.47.
2. VERTICAL CONTROL IS MEAN-LOWER-LOW-WATER (MLLW = 0.0') IN U.S. SURVEY FEET BASED ON NOAA/NOS TIDAL DATUM "9455920 ANCHORAGE, KNIK ARM, COOK INLET, ALASKA", PUBLISHED 04/21/2003, HOLDING USCGS SBC "B 75 1964" AS 36.82' AND NOAA/NOS TIDAL DATUM "9455912 FIRE ISLAND, ALASKA", PUBLISHED 05/21/2004, HOLDING NOS SBC "BM 13 1974" AS 28.41'. (SEE NOTE 4)
3. THIS SURVEY WAS CONDUCTED AUGUST 17–20, 2007. SOUNDINGS WERE COLLECTED USING A RESON SEABAT 8101 MULTIBEAM ECHOSOUNDER SYSTEM WITH A 240KHZ, 150 DEGREE SWATH-WIDTH TRANSDUCER (101 – 1.5 DEGREE BEAMS). POSITIONING, VESSEL ATTITUDE, HEADING AND TIDES WERE PROVIDED IN REAL-TIME USING AN APPLANIX POS M/V INERTIAL ATTITUDE AND POSITIONING SYSTEM OPERATING ON KINEMATIC GPS CORRECTIONS BROADCAST FROM A TRIMBLE 7400MSI RTK BASE RECEIVER SET AT "TERRA-9 2005", LOCATED ATOP THE PORT OF ANCHORAGE ADMINISTRATION BUILDING. SOUND VELOCITY WAS MEASURED AND APPLIED USING AN ODOM DIGI-BAR PRO SOUND VELOCITY PROFILER DEPLOYED DURING THE SURVEY. REAL-TIME-KINEMATIC HEIGHT VALUES WERE CALIBRATED TO DIRECT MANUAL TIDE OBSERVATIONS HOLDING USCGS SBC "B 75 1964" LOCATED AT NOAA/NOS TIDE STATION "9455920" AT THE PORT OF ANCHORAGE (SEE NOTE 4). SURVEY LINE NAVIGATION AND DATA COLLECTION WERE CONDUCTED USING QPS QINSY (V7.5) INTEGRATED SOFTWARE. DATA PROCESSING WAS PERFORMED USING A COMBINATION OF QPS QINSY AND CARIS HIPS (V6.1) SOFTWARE.
4. THE SURVEY AND THE PRELIMINARY PROCESSED DATASET WAS BASED ON RTK MLLW TIDE DATUM AT THE PORT OF ANCHORAGE AS NOTED ABOVE. THE FINAL DATASET WAS ADJUSTED TO REFLECT THE DIFFERENCE IN TIDE DATUM VALUES AT THE PORT OF ANCHORAGE (NOAA/NOS 9455920) AND THE TIDE DATUM VALUES AT FIRE ISLAND (NOAA/NOS 9455912). THIS "TILTED PLANE" ADJUSTMENT WAS PERFORMED TO PROVIDE A UNIFORM MLLW BASED APPROACH FROM THE WEST END OF THE COOK INLET NAVIGATION CHANNEL INTO THE PORT OF ANCHORAGE. THE ADJUSTMENT IS BASED ON OBSERVED RTK HEIGHT VALUES MEASURED AT BOTH NOAA/NOS TIDE STATIONS LISTED ABOVE. THE OBSERVED RTK DIFFERENCE HOLDS THE PORT OF ANCHORAGE AT 0.0' AND FIRE ISLAND AT −3.73'. THE ADJUSTMENT WAS PERFORMED USING A PROPRIETARY "LINEAR INTERPOLATION VERTICAL ADJUSTMENT ROUTINE" RAISING ALL SOUNDINGS PROPORTIONATELY ALONG THE DISTANCE BETWEEN THE TIDAL BENCH MARKS UTILIZED TO DEFINE THE VERTICAL DATUM. THE ADJUSTMENT AT THE PORT OF ANCHORAGE IS 0.0' EXTENDING TO AN ADJUSTMENT OF +3.73' AT FIRE ISLAND (SEE DIAGRAM SHEET 1).
5. SOUNDINGS ARE IN U.S. SURVEY FEET AND ARE MINUS UNLESS NOTED OTHERWISE.
6. THIS DRAWING IS INDICATIVE OF CONDITIONS AT THE TIME OF SURVEY.
7. NO NEW HORIZONTAL OR VERTICAL CONTROL MONUMENTS WERE ESTABLISHED DURING THIS SURVEY.

COOK INLET NAVIGATION CHANNEL COORDINATES

CHANNEL CENTERLINE

COR.	NORTHING	EASTING	STATION	DESCRIPTION
CL1	2,626,865.50	1,613,018.09	0+00	CENTERLINE WORONZOF RANGELINE
CL2	2,628,048.21	1,619,409.58	65+00	WORONZOF/FIRE ISLAND RANGELINE INTERSECTION
CL3	2,639,188.27	1,640,441.44	303+00	FIRE ISLAND/TRANSITION TO POA APPROACH
CL4	2,641,712.17	1,650,169.36	403+50	POA APPROACH
CL5	2,644,429.31	1,655,293.53	461+50	CENTERLINE POA APPROACH

CHANNEL LIMITS

COR.	NORTHING	EASTING	STATION	COR.	NORTHING	EASTING	STATION
NC1	2,627,365.51	1,612,925.56		NC6	2,638,711.03	1,640,626.80	
NC2	2,628,534.04	1,619,240.43		NC7	2,642,189.38	1,649,983.88	
NC3	2,639,665.52	1,640,256.07		NC8	2,644,878.56	1,655,055.31	
NC4	2,626,365.49	1,613,110.61		NC9	2,641,234.95	1,650,354.84	
NC5	2,627,562.38	1,619,578.73		NC10	2,643,980.06	1,655,531.75	

SURVEY LIMITS

CORNER	NORTHING	EASTING	CORNER	NORTHING	EASTING
SL1	2,628,340.46	1,612,745.15	SL6	2,637,780.48	1,640,988.24
SL2	2,629,481.34	1,618,910.61	SL7	2,643,119.87	1,649,622.22
SL3	2,641,596.07	1,639,894.63	SL8	2,645,754.53	1,654,590.82
SL4	2,625,390.54	1,613,291.02	SL9	2,640,304.46	1,650,716.50
SL5	2,626,615.08	1,619,908.55	SL10	2,643,104.09	1,655,996.24

△ CONTROL COORDINATES △

STATION	NORTHING	EASTING	ELEVATION	DESCRIPTION
N END 1978	2,646,652.19	1,660,582.43	41.39	USACE SBC
S END 1978	2,644,295.69	1,659,728.19	40.37	USACE SBC
TERRA-9 2005	2,644,992.51	1,660,164.06	80.38	PORT OFFICE ANT. MOUNT
PORT 1989	2,639,936.64	1,656,922.51	39.93	USACE SAC
EQ-1	2,629,995.41	1,643,787.75	–	–
VAN DUSEN GPS 1986	2,621,198.82	1,648,753.69	–	NGS SBC
AWWU 1994	2,629,310.76	1,635,837.68	–	3" ALCAP
NOAA/NOS TIDAL BENCH MARKS AT THE PORT OF ANCHORAGE 9455920				
TIDAL 16 1966	2,644,293	1,659,727	40.53	USCGS BENCH MARK SBC
B 75 1964	2,644,598	1,660,095	36.82	USCGS BENCH MARK SBC
NOAA/NOS TIDAL BENCH MARKS AT FIRE ISLAND 945912				
BM 13 1974	2,620,685	1,605,138	28.41	NOS TIDAL BENCH MARK SBC
RIFE 1960	2,620,520	1,604,180	29.99	USCGS TRI-STA SBC

CONTRACT NO. W911KB-07-D-0005

CONTRACTOR TERRA SURVEYS, LLC

CITY PALMER STATE ALASKA

ALASKA DISTRICT
CORPS OF ENGINEERS
ANCHORAGE, ALASKA

SURVEYED: SC/SM/CM
DRAWN: S. LEATHAM
CHECKED: KDW
SUBMITTED:

ANCHORAGE, ALASKA
COOK INLET NAVIGATION CHANNEL
PROJECT CONDITION SURVEY
AUGUST 17–20, 2007

RECOMMENDED: PROJECT MANAGER

APPROVED: CHIEF OPERATIONS-READINESS BRANCH

DATE:

SURVEY NO. 2477-07

SCALE: 1" = 200'

SHEET 6 OF 11





NOTES

1. HORIZONTAL CONTROL IS ALASKA STATE PLANE, ZONE 4, NAD83 IN U.S. SURVEY FEET HOLDING USACE SBC "N END 1978" AS N 2,646,652.19, E 1,660,582.43 AND USACE SBC "S END 1978" AS N 2,644,298.25, E 1,659,725.47.
2. VERTICAL CONTROL IS MEAN–LOWER–LOW–WATER (MLLW = 0.0') IN U.S. SURVEY FEET BASED ON NOAA/NOS TIDAL DATUM "9455920 ANCHORAGE, KNIK ARM, COOK INLET, ALASKA", PUBLISHED 04/21/2003, HOLDING USCGS SBC "B 75 1964" AS 36.82' AND NOAA/NOS TIDAL DATUM "9455912 FIRE ISLAND, ALASKA", PUBLISHED 05/21/2004, HOLDING NOS SBC "BM 13 1974" AS 28.41'. (SEE NOTE 4)
3. THIS SURVEY WAS CONDUCTED AUGUST 17–20, 2007. SOUNDINGS WERE COLLECTED USING A RESON SEABAT 8101 MULTIBEAM ECHOSOUNDER SYSTEM WITH A 240kHZ, 150 DEGREE SWATH–WIDTH TRANSDUCER (101 – 1.5 DEGREE BEAMS). POSITIONING, VESSEL ATTITUDE, HEADING AND TIDES WERE PROVIDED IN REAL–TIME USING AN APPLANIX POS M/V INERTIAL ATTITUDE AND POSITIONING SYSTEM OPERATING ON KINEMATIC GPS CORRECTIONS BROADCAST FROM A TRIMBLE 7400MSI RTK BASE RECEIVER SET AT "TERRA–9 2005", LOCATED ATOP THE PORT OF ANCHORAGE ADMINISTRATION BUILDING. SOUND VELOCITY WAS MEASURED AND APPLIED USING AN ODOM DIGI–BAR PRO SOUND VELOCITY PROFILER DEPLOYED DURING THE SURVEY. REAL–TIME–KINEMATIC HEIGHT VALUES WERE CALIBRATED TO DIRECT MANUAL TIDE OBSERVATIONS HOLDING USCGS SBC "B 75 1964" LOCATED AT NOAA/NOS TIDE STATION "9455920" AT THE PORT OF ANCHORAGE (SEE NOTE 4). SURVEY LINE NAVIGATION AND DATA COLLECTION WERE CONDUCTED USING QPS QINSY (V7.5) INTEGRATED SOFTWARE. DATA PROCESSING WAS PERFORMED USING A COMBINATION OF QPS QINSY AND CARIS HIPS (V6.1) SOFTWARE.
4. THE SURVEY AND THE PRELIMINARY PROCESSED DATASET WAS BASED ON RTK MLLW TIDE DATUM AT THE PORT OF ANCHORAGE AS NOTED ABOVE. THE FINAL DATASET WAS ADJUSTED TO REFLECT THE DIFFERENCE IN TIDE DATUM VALUES AT THE PORT OF ANCHORAGE (NOAA/NOS 9455920) AND THE TIDE DATUM VALUES AT FIRE ISLAND (NOAA/NOS 9455912). THIS "TILTED PLANE" ADJUSTMENT WAS PERFORMED TO PROVIDE A UNIFORM MLLW BASED APPROACH FROM THE WEST END OF THE COOK INLET NAVIGATION CHANNEL INTO THE PORT OF ANCHORAGE. THE ADJUSTMENT IS BASED ON OBSERVED RTK HEIGHT VALUES MEASURED AT BOTH NOAA/NOS TIDE STATIONS LISTED ABOVE. THE OBSERVED RTK DIFFERENCE HOLDS THE PORT OF ANCHORAGE AT 0.0' AND FIRE ISLAND AT −3.73'. THE ADJUSTMENT WAS PERFORMED USING A PROPRIETARY "LINEAR INTERPOLATION VERTICAL ADJUSTMENT ROUTINE" RAISING ALL SOUNDINGS PROPORTIONATELY ALONG THE DISTANCE BETWEEN THE TIDAL BENCH MARKS UTILIZED TO DEFINE THE VERTICAL DATUM. THE ADJUSTMENT AT THE PORT OF ANCHORAGE IS 0.0' EXTENDING TO AN ADJUSTMENT OF +3.73' AT FIRE ISLAND (SEE DIAGRAM SHEET 1).
5. SOUNDINGS ARE IN U.S. SURVEY FEET AND ARE MINUS UNLESS NOTED OTHERWISE.
6. THIS DRAWING IS INDICATIVE OF CONDITIONS AT THE TIME OF SURVEY.
7. NO NEW HORIZONTAL OR VERTICAL CONTROL MONUMENTS WERE ESTABLISHED DURING THIS SURVEY.

COOK INLET NAVIGATION CHANNEL COORDINATES

CHANNEL CENTERLINE

COR.	NORTHING	EASTING	STATION	DESCRIPTION
CL1	2,626,865.50	1,613,018.09	0+00	CENTERLINE WORONZOF RANGELINE
CL2	2,628,048.21	1,619,409.58	65+00	WORONZOF/FIRE ISLAND RANGELINE INTERSECTION
CL3	2,639,188.27	1,640,441.44	303+00	FIRE ISLAND/TRANSITION TO POA APPROACH
CL4	2,641,712.17	1,650,169.36	403+50	POA APPROACH
CL5	2,644,429.31	1,655,293.53	461+50	CENTERLINE POA APPROACH

CHANNEL LIMITS

COR.	NORTHING	EASTING	STATION	COR.	NORTHING	EASTING	STATION
NC1	2,627,365.51	1,612,925.56		NC6	2,638,711.03	1,640,626.80	
NC2	2,628,534.04	1,619,240.43		NC7	2,642,189.38	1,649,983.88	
NC3	2,639,665.52	1,640,256.07		NC8	2,644,878.56	1,655,055.31	
NC4	2,626,365.49	1,613,110.61		NC9	2,641,234.95	1,650,354.84	
NC5	2,627,562.38	1,619,578.73		NC10	2,643,980.06	1,655,531.75	

SURVEY LIMITS

CORNER	NORTHING	EASTING	CORNER	NORTHING	EASTING
SL1	2,628,340.46	1,612,745.15	SL6	2,637,780.48	1,640,988.24
SL2	2,629,481.34	1,618,910.61	SL7	2,643,119.87	1,649,622.22
SL3	2,641,596.07	1,639,894.63	SL8	2,645,754.53	1,654,590.82
SL4	2,625,390.54	1,613,291.02	SL9	2,640,304.46	1,650,716.50
SL5	2,626,615.08	1,619,908.55	SL10	2,643,104.09	1,655,996.24

⚠ CONTROL COORDINATES ⚠

STATION	NORTHING	EASTING	ELEVATION	DESCRIPTION
N END 1978	2,646,652.19	1,660,582.43	41.39	USACE SBC
S END 1978	2,644,295.69	1,659,728.19	40.37	USACE SBC
TERRA–9 2005	2,644,992.51	1,660,164.06	80.38	PORT OFFICE ANT. MOUNT
PORT 1989	2,639,936.64	1,656,922.51	39.93	USACE SAC
EQ–1	2,629,995.41	1,643,787.75	–	–
VAN DUSEN GPS 1986	2,621,198.82	1,648,753.69	–	NGS SBC
AWWJ 1994	2,629,310.76	1,635,837.68	–	3" ALCAP
NOAA/NOS TIDAL BENCH MARKS AT THE PORT OF ANCHORAGE 9455920				
TIDAL 16 1966	2,644,293	1,659,727	40.53	USCGS BENCH MARK SBC
B 75 1964	2,644,598	1,660,095	36.82	USCGS BENCH MARK SBC
NOAA/NOS TIDAL BENCH MARKS AT FIRE ISLAND 9455912				
BM 13 1974	2,620,685	1,605,138	28.41	NOS TIDAL BENCH MARK SBC
RIFE 1960	2,620,520	1,604,180	29.99	USCGS TRI–STA SBC

CONTRACT NO. W911KB–07–D–0005
CONTRACTOR TERRA SURVEYS, LLC
CITY PALMER STATE ALASKA

ALASKA DISTRICT
CORPS OF ENGINEERS
ANCHORAGE, ALASKA

SURVEYED: SC/SM/CM
DRAWN: S. LEATHAM
CHECKED: KDW
SUBMITTED:

ANCHORAGE, ALASKA
COOK INLET NAVIGATION CHANNEL
PROJECT CONDITION SURVEY
AUGUST 17–20, 2007

RECOMMENDED: PROJECT MANAGER
APPROVED: CHIEF OPERATIONS–READINESS BRANCH
DATE:

SURVEY NO. 2477–07

SCALE: 1" = 200'

SHEET 7 OF 11





NOTES

1. HORIZONTAL CONTROL IS ALASKA STATE PLANE, ZONE 4, NAD83 IN U.S. SURVEY FEET HOLDING USACE SBC "N END 1978" AS N 2,646,652.19, E 1,660,582.43 AND USACE SBC "S END 1978" AS N 2,644,298.25, E 1,659,725.47.
2. VERTICAL CONTROL IS MEAN-LOWER-LOW-WATER (MLLW = 0.0') IN U.S. SURVEY FEET BASED ON NOAA/NOS TIDAL DATUM "9455920 ANCHORAGE, KNIK ARM, COOK INLET, ALASKA", PUBLISHED 04/21/2003, HOLDING USCGS SBC "B 75 1964" AS 36.82' AND NOAA/NOS TIDAL DATUM "9455912 FIRE ISLAND, ALASKA", PUBLISHED 05/21/2004, HOLDING NOS SBC "BM 13 1974" AS 28.41'. (SEE NOTE 4)
3. THIS SURVEY WAS CONDUCTED AUGUST 17–20, 2007. SOUNDINGS WERE COLLECTED USING A RESON SEABAT 8101 MULTIBEAM ECHOSOUNDER SYSTEM WITH A 240KHZ, 150 DEGREE SWATH-WIDTH TRANSDUCER (101 – 1.5 DEGREE BEAMS). POSITIONING, VESSEL ATTITUDE, HEADING AND TIDES WERE PROVIDED IN REAL-TIME USING AN APPLANIX POS M/V INERTIAL ATTITUDE AND POSITIONING SYSTEM OPERATING ON KINEMATIC GPS CORRECTIONS BROADCAST FROM A TRIMBLE 7400MSI RTK BASE RECEIVER SET AT "TERRA-9 2005", LOCATED ATOP THE PORT OF ANCHORAGE ADMINISTRATION BUILDING. SOUND VELOCITY WAS MEASURED AND APPLIED USING AN ODOM DIGI-BAR PRO SOUND VELOCITY PROFILER DEPLOYED DURING THE SURVEY. REAL-TIME-KINEMATIC HEIGHT VALUES WERE CALIBRATED TO DIRECT MANUAL TIDE OBSERVATIONS HOLDING USCGS SBC "B 75 1964" LOCATED AT NOAA/NOS TIDE STATION "9455920" AT THE PORT OF ANCHORAGE (SEE NOTE 4). SURVEY LINE NAVIGATION AND DATA COLLECTION WERE CONDUCTED USING QPS QINSY (V7.5) INTEGRATED SOFTWARE. DATA PROCESSING WAS PERFORMED USING A COMBINATION OF QPS QINSY AND CARIS HIPS (V6.1) SOFTWARE.
4. THE SURVEY AND THE PRELIMINARY PROCESSED DATASET WAS BASED ON RTK MLLW TIDE DATUM AT THE PORT OF ANCHORAGE AS NOTED ABOVE. THE FINAL DATASET WAS ADJUSTED TO REFLECT THE DIFFERENCE IN TIDE DATUM VALUES AT THE PORT OF ANCHORAGE (NOAA/NOS 9455920) AND THE TIDE DATUM VALUES AT FIRE ISLAND (NOAA/NOS 9455912). THIS "TILTED PLANE" ADJUSTMENT WAS PERFORMED TO PROVIDE A UNIFORM MLLW BASED APPROACH FROM THE WEST END OF THE COOK INLET NAVIGATION CHANNEL INTO THE PORT OF ANCHORAGE. THE ADJUSTMENT IS BASED ON OBSERVED RTK HEIGHT VALUES MEASURED AT BOTH NOAA/NOS TIDE STATIONS LISTED ABOVE. THE OBSERVED RTK DIFFERENCE HOLDS THE PORT OF ANCHORAGE AT 0.0' AND FIRE ISLAND AT −3.73'. THE ADJUSTMENT WAS PERFORMED USING A PROPRIETARY "LINEAR INTERPOLATION VERTICAL ADJUSTMENT ROUTINE" RAISING ALL SOUNDINGS PROPORTIONATELY ALONG THE DISTANCE BETWEEN THE TIDAL BENCH MARKS UTILIZED TO DEFINE THE VERTICAL DATUM. THE ADJUSTMENT AT THE PORT OF ANCHORAGE IS 0.0' EXTENDING TO AN ADJUSTMENT OF +3.73' AT FIRE ISLAND (SEE DIAGRAM SHEET 1).
5. SOUNDINGS ARE IN U.S. SURVEY FEET AND ARE MINUS UNLESS NOTED OTHERWSE.
6. THIS DRAWING IS INDICATIVE OF CONDITIONS AT THE TIME OF SURVEY.
7. NO NEW HORIZONTAL OR VERTICAL CONTROL MONUMENTS WERE ESTABLISHED DURING THIS SURVEY.

COOK INLET NAVIGATION CHANNEL COORDINATES

CHANNEL CENTERLINE

COR.	NORTHING	EASTING	STATION	DESCRIPTION
CL1	2,626,865.50	1,613,018.09	0+00	CENTERLINE WORONZOF RANGELINE
CL2	2,628,048.21	1,619,409.58	65+00	WORONZOF/FIRE ISLAND RANGELINE INTERSECTION
CL3	2,639,188.27	1,640,441.44	303+00	FIRE ISLAND/TRANSITION TO POA APPROACH
CL4	2,641,712.17	1,650,169.36	403+50	POA APPROACH
CL5	2,644,429.31	1,655,293.53	461+50	CENTERLINE POA APPROACH

CHANNEL LIMITS

COR.	NORTHING	EASTING	STATION	COR.	NORTHING	EASTING	STATION
NC1	2,627,365.51	1,612,925.56		NC6	2,638,711.03	1,640,626.80	
NC2	2,628,534.04	1,619,240.43		NC7	2,642,189.38	1,649,983.88	
NC3	2,639,665.52	1,640,256.07		NC8	2,644,878.56	1,655,055.31	
NC4	2,626,365.49	1,613,110.61		NC9	2,641,234.95	1,650,354.84	
NC5	2,627,562.38	1,619,578.73		NC10	2,643,980.06	1,655,531.75	

SURVEY LIMITS

CORNER	NORTHING	EASTING	CORNER	NORTHING	EASTING
SL1	2,628,340.46	1,612,745.15	SL6	2,637,780.48	1,640,988.24
SL2	2,629,481.34	1,618,910.61	SL7	2,643,119.87	1,649,622.22
SL3	2,641,596.07	1,639,894.63	SL8	2,645,754.53	1,654,590.82
SL4	2,625,390.54	1,613,291.02	SL9	2,640,304.46	1,650,716.50
SL5	2,626,615.08	1,619,908.55	SL10	2,643,104.09	1,655,996.24

△ CONTROL COORDINATES △

STATION	NORTHING	EASTING	ELEVATION	DESCRIPTION
N END 1978	2,646,652.19	1,660,582.43	41.39	USACE SBC
S END 1978	2,644,295.69	1,659,728.19	40.37	USACE SBC
TERRA-9 2005	2,644,992.51	1,660,164.06	80.38	PORT OFFICE ANT. MOUNT
PORT 1989	2,639,936.64	1,656,922.51	39.93	USACE SAC
EQ-1	2,629,995.41	1,643,787.75	–	–
VAN DUSEN GPS 1986	2,621,198.82	1,648,753.69	–	NGS SBC
AWWU 1994	2,629,310.76	1,635,837.68	–	3" ALCAP
NOAA/NOS TIDAL BENCH MARKS AT THE PORT OF ANCHORAGE 9455920				
TIDAL 16 1966	2,644,293	1,659,727	40.53	USCGS BENCH MARK SBC
B 75 1964	2,644,598	1,660,095	36.82	USCGS BENCH MARK SBC
NOAA/NOS TIDAL BENCH MARKS AT FIRE ISLAND 945591				
BM 13 1974	2,620,685	1,605,138	28.41	NOS TIDAL BENCH MARK SBC
RIFE 1960	2,620,520	1,604,180	29.99	USCGS TRI-STA SBC

CONTRACT NO. W911KB-07-D-0005
CONTRACTOR TERRA SURVEYS, LLC
CITY PALMER STATE ALASKA

ALASKA DISTRICT
CORPS OF ENGINEERS
ANCHORAGE, ALASKA

SURVEYED: SC/SM/CM
DRAWN: S. LEATHAM
CHECKED: KDW
SUBMITTED:

ANCHORAGE, ALASKA
COOK INLET NAVIGATION CHANNEL
PROJECT CONDITION SURVEY
AUGUST 17–20, 2007

RECOMMENDED: PROJECT MANAGER
APPROVED: CHIEF OPERATIONS-READINESS BRANCH
DATE:

SURVEY NO. 2477-07

SCALE: 1" = 200'

SHEET 8 OF 11





NOTES

1. HORIZONTAL CONTROL IS ALASKA STATE PLANE, ZONE 4, NAD83 IN U.S. SURVEY FEET HOLDING USACE SBC "N END 1978" AS N 2,646,652.19, E 1,660,582.43 AND USACE SBC "S END 1978" AS N 2,644,298.25, E 1,659,725.47.
2. VERTICAL CONTROL IS MEAN–LOWER–LOW–WATER (MLLW = 0.0') IN U.S. SURVEY FEET BASED ON NOAA/NOS TIDAL DATUM "9455920 ANCHORAGE, KNIK ARM, COOK INLET, ALASKA", PUBLISHED 04/21/2003, HOLDING USCGS SBC "B 75 1964" AS 36.82' AND NOAA/NOS TIDAL DATUM "9455912 FIRE ISLAND, ALASKA", PUBLISHED 05/21/2004, HOLDING NOS SBC "BM 13 1974" AS 28.41'. (SEE NOTE 4)
3. THIS SURVEY WAS CONDUCTED AUGUST 17–20, 2007. SOUNDINGS WERE COLLECTED USING A RESON SEABAT 8101 MULTIBEAM ECHOSOUNDER SYSTEM WITH A 240kHZ, 150 DEGREE SWATH–WIDTH TRANSDUCER (101 – 1.5 DEGREE BEAMS). POSITIONING, VESSEL ATTITUDE, HEADING AND TIDES WERE PROVIDED IN REAL–TIME USING AN APPLANIX POS M/V INERTIAL ATTITUDE AND POSITIONING SYSTEM OPERATING ON KINEMATIC GPS CORRECTIONS BROADCAST FROM A TRIMBLE 7400MSI RTK BASE RECEIVER SET AT "TERRA–9 2005", LOCATED ATOP THE PORT OF ANCHORAGE ADMINISTRATION BUILDING. SOUND VELOCITY WAS MEASURED AND APPLIED USING AN ODOM DIGI–BAR PRO SOUND VELOCITY PROFILER DEPLOYED DURING THE SURVEY. REAL–TIME–KINEMATIC HEIGHT VALUES WERE CALIBRATED TO DIRECT MANUAL TIDE OBSERVATIONS HOLDING USCGS SBC "B 75 1964" LOCATED AT NOAA/NOS TIDE STATION "9455920" AT THE PORT OF ANCHORAGE (SEE NOTE 4). SURVEY LINE NAVIGATION AND DATA COLLECTION WERE CONDUCTED USING QPS QINSY (V7.5) INTEGRATED SOFTWARE. DATA PROCESSING WAS PERFORMED USING A COMBINATION OF QPS QINSY AND CARIS HIPS (V6.1) SOFTWARE.
4. THE SURVEY AND THE PRELIMINARY PROCESSED DATASET WAS BASED ON RTK MLLW TIDE DATUM AT THE PORT OF ANCHORAGE AS NOTED ABOVE. THE FINAL DATASET WAS ADJUSTED TO REFLECT THE DIFFERENCE IN TIDE DATUM VALUES AT THE PORT OF ANCHORAGE (NOAA/NOS 9455920) AND THE TIDE DATUM VALUES AT FIRE ISLAND (NOAA/NOS 9455912). THIS "TILTED PLANE" ADJUSTMENT WAS PERFORMED TO PROVIDE A UNIFORM MLLW BASED APPROACH FROM THE WEST END OF THE COOK INLET NAVIGATION CHANNEL INTO THE PORT OF ANCHORAGE. THE ADJUSTMENT IS BASED ON OBSERVED RTK HEIGHT VALUES MEASURED AT BOTH NOAA/NOS TIDE STATIONS LISTED ABOVE. THE OBSERVED RTK DIFFERENCE HOLDS THE PORT OF ANCHORAGE AT 0.0' AND FIRE ISLAND AT −3.73'. THE ADJUSTMENT WAS PERFORMED USING A PROPRIETARY "LINEAR INTERPOLATION VERTICAL ADJUSTMENT ROUTINE" RAISING ALL SOUNDINGS PROPORTIONATELY ALONG THE DISTANCE BETWEEN THE TIDAL BENCH MARKS UTILIZED TO DEFINE THE VERTICAL DATUM. THE ADJUSTMENT AT THE PORT OF ANCHORAGE IS 0.0' EXTENDING TO AN ADJUSTMENT OF +3.73' AT FIRE ISLAND (SEE DIAGRAM SHEET 1).
5. SOUNDINGS ARE IN U.S. SURVEY FEET AND ARE MINUS UNLESS NOTED OTHERWISE.
6. THIS DRAWING IS INDICATIVE OF CONDITIONS AT THE TIME OF SURVEY.
7. NO NEW HORIZONTAL OR VERTICAL CONTROL MONUMENTS WERE ESTABLISHED DURING THIS SURVEY.

COOK INLET NAVIGATION CHANNEL COORDINATES

CHANNEL CENTERLINE

COR.	NORTHING	EASTING	STATION	DESCRIPTION
CL1	2,626,865.50	1,613,018.09	0+00	CENTERLINE WORONZOF RANGELINE
CL2	2,628,048.21	1,619,409.58	65+00	WORONZOF/FIRE ISLAND RANGELINE INTERSECTION
CL3	2,639,188.27	1,640,441.44	303+00	FIRE ISLAND/TRANSITION TO POA APPROACH
CL4	2,641,712.17	1,650,169.36	403+50	POA APPROACH
CL5	2,644,429.31	1,655,293.53	461+50	CENTERLINE POA APPROACH

CHANNEL LIMITS

COR.	NORTHING	EASTING	STATION	COR.	NORTHING	EASTING	STATION
NC1	2,627,365.51	1,612,925.56		NC6	2,638,711.03	1,640,626.80	
NC2	2,628,534.04	1,619,240.43		NC7	2,642,189.38	1,649,983.88	
NC3	2,639,665.52	1,640,256.07		NC8	2,644,878.56	1,655,055.31	
NC4	2,626,365.49	1,613,110.61		NC9	2,641,234.95	1,650,354.84	
NC5	2,627,562.38	1,619,578.73		NC10	2,643,980.06	1,655,531.75	

SURVEY LIMITS

CORNER	NORTHING	EASTING	CORNER	NORTHING	EASTING
SL1	2,628,340.46	1,612,745.15	SL6	2,637,780.48	1,640,988.24
SL2	2,629,481.34	1,618,910.61	SL7	2,643,119.87	1,649,622.22
SL3	2,641,596.07	1,639,894.63	SL8	2,645,754.53	1,654,590.82
SL4	2,625,390.54	1,613,291.02	SL9	2,640,304.46	1,650,716.50
SL5	2,626,615.08	1,619,908.55	SL10	2,643,104.09	1,655,996.24

△ CONTROL COORDINATES △

STATION	NORTHING	EASTING	ELEVATION	DESCRIPTION
N END 1978	2,646,652.19	1,660,582.43	41.39	USACE SBC
S END 1978	2,644,295.69	1,659,728.19	40.37	USACE SBC
TERRA–9 2005	2,644,992.51	1,660,164.06	80.38	PORT OFFICE ANT. MOUNT
PORT 1989	2,639,936.64	1,656,922.51	39.93	USACE SAC
EQ–1	2,629,995.41	1,643,787.75	–	–
VAN DUSEN GPS 1986	2,621,198.82	1,648,753.69	–	NGS SBC
AWWU 1994	2,629,310.76	1,635,837.68	–	3" ALCAP
NOAA/NOS TIDAL BENCH MARKS AT THE PORT OF ANCHORAGE 9455920				
TIDAL 16 1966	2,644,293	1,659,727	40.53	USCGS BENCH MARK SBC
B 75 1964	2,644,598	1,660,095	36.82	USCGS BENCH MARK SBC
NOAA/NOS TIDAL BENCH MARKS AT FIRE ISLAND 9455912				
BM 13 1974	2,620,685	1,605,138	28.41	NOS TIDAL BENCH MARK SBC
RIFE 1960	2,620,520	1,604,180	29.99	USCGS TRI–STA SBC

CONTRACT NO. W911KB–07–D–0005
CONTRACTOR TERRA SURVEYS, LLC
CITY PALMER STATE ALASKA

ALASKA DISTRICT
CORPS OF ENGINEERS
ANCHORAGE, ALASKA

SURVEYED: SC/SM/CM
DRAWN: S. LEATHAM
CHECKED: KDW
SUBMITTED:

ANCHORAGE, ALASKA
COOK INLET NAVIGATION CHANNEL
PROJECT CONDITION SURVEY
AUGUST 17–20, 2007

RECOMMENDED: PROJECT MANAGER
APPROVED: CHIEF OPERATIONS–READINESS BRANCH
DATE:

SURVEY NO. 2477–07

SCALE: 1" = 200'

SHEET 9 OF 11

U. S. ARMY





NOTES

1. HORIZONTAL CONTROL IS ALASKA STATE PLANE, ZONE 4, NAD83 IN U.S. SURVEY FEET HOLDING USACE SBC "N END 1978" AS N 2,646,652.19, E 1,660,582.43 AND USACE SBC "S END 1978" AS N 2,644,298.25, E 1,659,725.47.
2. VERTICAL CONTROL IS MEAN-LOWER-LOW-WATER (MLLW = 0.0') IN U.S. SURVEY FEET BASED ON NOAA/NOS TIDAL DATUM "9455920 ANCHORAGE, KNIK ARM, COOK INLET, ALASKA", PUBLISHED 04/21/2003, HOLDING USCGS SBC "B 75 1964" AS 36.82' AND NOAA/NOS TIDAL DATUM "9455912 FIRE ISLAND, ALASKA", PUBLISHED 05/21/2004, HOLDING NOS SBC "BM 13 1974" AS 28.41'. (SEE NOTE 4)
3. THIS SURVEY WAS CONDUCTED AUGUST 17–20, 2007. SOUNDINGS WERE COLLECTED USING A RESON SEABAT 8101 MULTIBEAM ECHOSOUNDER SYSTEM WITH A 240KHZ, 150 DEGREE SWATH-WIDTH TRANSDUCER (101 – 1.5 DEGREE BEAMS). POSITIONING, VESSEL ATTITUDE, HEADING AND TIDES WERE PROVIDED IN REAL-TIME USING AN APPLANIX POS M/V INERTIAL ATTITUDE AND POSITIONING SYSTEM OPERATING ON KINEMATIC GPS CORRECTIONS BROADCAST FROM A TRIMBLE 7400MSI RTK BASE RECEIVER SET AT "TERRA-9 2005", LOCATED ATOP THE PORT OF ANCHORAGE ADMINISTRATION BUILDING. SOUND VELOCITY WAS MEASURED AND APPLIED USING AN ODOM DIGI-BAR PRO SOUND VELOCITY PROFILER DEPLOYED DURING THE SURVEY. REAL-TIME-KINEMATIC HEIGHT VALUES WERE CALIBRATED TO DIRECT MANUAL TIDE OBSERVATIONS HOLDING USCGS SBC "B 75 1964" LOCATED AT NOAA/NOS TIDE STATION "9455920" AT THE PORT OF ANCHORAGE (SEE NOTE 4). SURVEY LINE NAVIGATION AND DATA COLLECTION WERE CONDUCTED USING QPS QINSY (V7.5) INTEGRATED SOFTWARE. DATA PROCESSING WAS PERFORMED USING A COMBINATION OF QPS QINSY AND CARIS HIPS (V6.1) SOFTWARE.
4. THE SURVEY AND THE PRELIMINARY PROCESSED DATASET WAS BASED ON RTK MLLW TIDE DATUM AT THE PORT OF ANCHORAGE AS NOTED ABOVE. THE FINAL DATASET WAS ADJUSTED TO REFLECT THE DIFFERENCE IN TIDE DATUM VALUES AT THE PORT OF ANCHORAGE (NOAA/NOS 9455920) AND THE TIDE DATUM VALUES AT FIRE ISLAND (NOAA/NOS 9455912). THIS "TILTED PLANE" ADJUSTMENT WAS PERFORMED TO PROVIDE A UNIFORM MLLW BASED APPROACH FROM THE WEST END OF THE COOK INLET NAVIGATION CHANNEL INTO THE PORT OF ANCHORAGE. THE ADJUSTMENT IS BASED ON OBSERVED RTK HEIGHT VALUES MEASURED AT BOTH NOAA/NOS TIDE STATIONS LISTED ABOVE. THE OBSERVED RTK DIFFERENCE HOLDS THE PORT OF ANCHORAGE AT 0.0' AND FIRE ISLAND AT –3.73'. THE ADJUSTMENT WAS PERFORMED USING A PROPRIETARY "LINEAR INTERPOLATION VERTICAL ADJUSTMENT ROUTINE" RAISING ALL SOUNDINGS PROPORTIONATELY ALONG THE DISTANCE BETWEEN THE TIDAL BENCH MARKS UTILIZED TO DEFINE THE VERTICAL DATUM. THE ADJUSTMENT AT THE PORT OF ANCHORAGE IS 0.0' EXTENDING TO AN ADJUSTMENT OF +3.73' AT FIRE ISLAND (SEE DIAGRAM SHEET 1).
5. SOUNDINGS ARE IN U.S. SURVEY FEET AND ARE MINUS UNLESS NOTED OTHERWISE.
6. THIS DRAWING IS INDICATIVE OF CONDITIONS AT THE TIME OF SURVEY.
7. NO NEW HORIZONTAL OR VERTICAL CONTROL MONUMENTS WERE ESTABLISHED DURING THIS SURVEY.

COOK INLET NAVIGATION CHANNEL COORDINATES

CHANNEL CENTERLINE

COR.	NORTHING	EASTING	STATION	DESCRIPTION
CL1	2,626,865.50	1,613,018.09	0+00	CENTERLINE WORONZOF RANGELINE
CL2	2,628,048.21	1,619,409.58	65+00	WORONZOF/FIRE ISLAND RANGELINE INTERSECTION
CL3	2,639,188.27	1,640,441.44	303+00	FIRE ISLAND/TRANSITION TO POA APPROACH
CL4	2,641,712.17	1,650,169.36	403+50	POA APPROACH
CL5	2,644,429.31	1,655,293.53	461+50	CENTERLINE POA APPROACH

CHANNEL LIMITS

COR.	NORTHING	EASTING	STATION	COR.	NORTHING	EASTING	STATION
NC1	2,627,365.51	1,612,925.56		NC6	2,638,711.03	1,640,626.80	
NC2	2,628,534.04	1,619,240.43		NC7	2,642,189.38	1,649,983.88	
NC3	2,639,665.52	1,640,256.07		NC8	2,644,878.56	1,655,055.31	
NC4	2,626,365.49	1,613,110.61		NC9	2,641,234.95	1,650,354.84	
NC5	2,627,562.38	1,619,578.73		NC10	2,643,980.06	1,655,531.75	

SURVEY LIMITS

CORNER	NORTHING	EASTING	CORNER	NORTHING	EASTING
SL1	2,628,340.46	1,612,745.15	SL6	2,637,780.48	1,640,988.24
SL2	2,629,481.34	1,618,910.61	SL7	2,643,119.87	1,649,622.22
SL3	2,641,596.07	1,639,894.63	SL8	2,645,754.53	1,654,590.82
SL4	2,625,390.54	1,613,291.02	SL9	2,640,304.46	1,650,716.50
SL5	2,626,615.08	1,619,908.55	SL10	2,643,104.09	1,655,996.24

△ CONTROL COORDINATES △

STATION	NORTHING	EASTING	ELEVATION	DESCRIPTION
N END 1978	2,646,652.19	1,660,582.43	41.39	USACE SBC
S END 1978	2,644,295.69	1,659,728.19	40.37	USACE SBC
TERRA-9 2005	2,644,992.51	1,660,164.06	80.38	PORT OFFICE ANT. MOUNT
PORT 1989	2,639,936.64	1,656,922.51	39.93	USACE SAC
EQ-1	2,629,995.41	1,643,787.75	–	–
VAN DUSEN GPS 1986	2,621,198.82	1,648,753.69	–	NGS SBC
AWWU 1994	2,629,310.76	1,635,837.68	–	3" ALCAP
NOAA/NOS TIDAL BENCH MARKS AT THE PORT OF ANCHORAGE 9455920				
TIDAL 16 1966	2,644,293	1,659,727	40.53	USCGS BENCH MARK SBC
B 75 1964	2,644,598	1,660,095	36.82	USCGS BENCH MARK SBC
NOAA/NOS TIDAL BENCH MARKS AT FIRE ISLAND 9455912				
BM 13 1974	2,620,685	1,605,138	28.41	NOS TIDAL BENCH MARK SBC
RIFE 1960	2,620,520	1,604,180	29.99	USCGS TRI-STA SBC

POA – DISPOSAL SITE LIMITS

CORNER	NORTHING	EASTING	CORNER	NORTHING	EASTING
D1	2,644,490.80	1,656,602.89	D3	2,641,671.82	1,655,576.56
D2	2,645,175.02	1,654,723.58	D4	2,642,356.04	1,653,697.24

CONTRACT NO. W911KB-07-D-0005
CONTRACTOR TERRA SURVEYS, LLC
CITY PALMER STATE ALASKA

ALASKA DISTRICT
CORPS OF ENGINEERS
ANCHORAGE, ALASKA

SURVEYED: SC/SM/CM
DRAWN: S. LEATHAM
CHECKED: KDW
SUBMITTED:

ANCHORAGE, ALASKA
COOK INLET NAVIGATION CHANNEL
PROJECT CONDITION SURVEY
AUGUST 17–20, 2007

RECOMMENDED: PROJECT MANAGER
APPROVED: CHIEF OPERATIONS-READINESS BRANCH
DATE:

SURVEY NO. 2477-07
SCALE: 1" = 200'
SHEET 10 OF 11



POA – DISPOSAL SITE LIMITS					
CORNER	NORTHING	EASTING	CORNER	NORTHING	EASTING
D1	2,644,490.80	1,656,602.89	D3	2,641,671.82	1,655,576.56
D2	2,645,175.02	1,654,723.58	D4	2,642,356.04	1,653,697.24



NOTES

1. HORIZONTAL CONTROL IS ALASKA STATE PLANE, ZONE 4, NAD83 IN U.S. SURVEY FEET HOLDING USACE SBC "N END 1978" AS N 2,646,652.19, E 1,660,582.43 AND USACE SBC "S END 1978" AS N 2,644,295.25, E 1,659,725.47.
2. VERTICAL CONTROL IS MEAN-LOWER-LOW-WATER (MLLW = 0.0') IN U.S. SURVEY FEET BASED ON NOAA/NOS TIDAL DATUM "9455920 ANCHORAGE, KNIK ARM, COOK INLET, ALASKA", PUBLISHED 04/21/2003, HOLDING USCGS SBC "B 75 1964" AS 36.82' AND NOAA/NOS TIDAL DATUM "9455912 FIRE ISLAND, ALASKA", PUBLISHED 05/21/2004, HOLDING NOS SBC "BM 13 1974" AS 28.41'. (SEE NOTE 4)
3. THIS SURVEY WAS CONDUCTED AUGUST 17–20, 2007. SOUNDINGS WERE COLLECTED USING A RESON SEABAT 8101 MULTIBEAM ECHOSOUNDER SYSTEM WITH A 240KHZ, 150 DEGREE SWATH-WIDTH TRANSDUCER (101 – 1.5 DEGREE BEAMS). POSITIONING, VESSEL ATTITUDE, HEADING AND TIDES WERE PROVIDED IN REAL-TIME USING AN APPLANIX POS M/V INERTIAL ATTITUDE AND POSITIONING SYSTEM OPERATING ON KINEMATIC GPS CORRECTIONS BROADCAST FROM A TRIMBLE 7400MSI RTK BASE RECEIVER SET AT "TERRA-9 2005", LOCATED ATOP THE PORT OF ANCHORAGE ADMINISTRATION BUILDING. SOUND VELOCITY WAS MEASURED AND APPLIED USING AN ODOM DIGI-BAR PRO SOUND VELOCITY PROFILER DEPLOYED DURING THE SURVEY. REAL-TIME-KINEMATIC HEIGHT VALUES WERE CALIBRATED TO DIRECT MANUAL TIDE OBSERVATIONS HOLDING USCGS SBC "B 75 1964" LOCATED AT NOAA/NOS TIDE STATION "9455920" AT THE PORT OF ANCHORAGE (SEE NOTE 4). SURVEY LINE NAVIGATION AND DATA COLLECTION WERE CONDUCTED USING QPS QINSY (V7.5) INTEGRATED SOFTWARE. DATA PROCESSING WAS PERFORMED USING A COMBINATION OF QPS QINSY AND CARIS HIPS (V6.1) SOFTWARE.
4. THE SURVEY AND THE PRELIMINARY PROCESSED DATASET WAS BASED ON RTK MLLW TIDE DATUM AT THE PORT OF ANCHORAGE AS NOTED ABOVE. THE FINAL DATASET WAS ADJUSTED TO REFLECT THE DIFFERENCE IN TIDE DATUM VALUES AT THE PORT OF ANCHORAGE (NOAA/NOS 9455920) AND THE TIDE DATUM VALUES AT FIRE ISLAND (NOAA/NOS 9455912). THIS "TILTED PLANE" ADJUSTMENT WAS PERFORMED TO PROVIDE A UNIFORM MLLW BASED APPROACH FROM THE WEST END OF THE COOK INLET NAVIGATION CHANNEL INTO THE PORT OF ANCHORAGE. THE ADJUSTMENT IS BASED ON OBSERVED RTK HEIGHT VALUES MEASURED AT BOTH NOAA/NOS TIDE STATIONS LISTED ABOVE. THE OBSERVED RTK DIFFERENCE HOLDS THE PORT OF ANCHORAGE AT 0.0' AND FIRE ISLAND AT −3.73'. THE ADJUSTMENT WAS PERFORMED USING A PROPRIETARY "LINEAR INTERPOLATION VERTICAL ADJUSTMENT ROUTINE" RAISING ALL SOUNDINGS PROPORTIONATELY ALONG THE DISTANCE BETWEEN THE TIDAL BENCH MARKS UTILIZED TO DEFINE THE VERTICAL DATUM. THE ADJUSTMENT AT THE PORT OF ANCHORAGE IS 0.0' EXTENDING TO AN ADJUSTMENT OF +3.73' AT FIRE ISLAND (SEE DIAGRAM SHEET 1).
5. SOUNDINGS ARE IN U.S. SURVEY FEET AND ARE MINUS UNLESS NOTED OTHERWISE.
6. THIS DRAWING IS INDICATIVE OF CONDITIONS AT THE TIME OF SURVEY.
7. NO NEW HORIZONTAL OR VERTICAL CONTROL MONUMENTS WERE ESTABLISHED DURING THIS SURVEY.

COOK INLET NAVIGATION CHANNEL COORDINATES									
CHANNEL CENTERLINE									
COR.	NORTHING	EASTING	STATION	DESCRIPTION					
CL1	2,626,865.50	1,613,018.09	0+00	CENTERLINE WORONZOF RANGELINE					
CL2	2,628,048.21	1,619,409.58	65+00	WORONZOF/FIRE ISLAND RANGELINE INTERSECTION					
CL3	2,639,188.27	1,640,441.44	303+00	FIRE ISLAND/TRANSITION TO POA APPROACH					
CL4	2,641,712.17	1,650,169.36	403+50	POA APPROACH					
CL5	2,644,429.31	1,655,293.53	461+50	CENTERLINE POA APPROACH					
CHANNEL LIMITS									
COR.	NORTHING	EASTING	STATION	COR.	NORTHING	EASTING	STATION		
NC1	2,627,365.51	1,612,925.56		NC6	2,638,711.03	1,640,626.80			
NC2	2,628,534.04	1,619,240.43		NC7	2,642,189.38	1,649,983.88			
NC3	2,639,665.52	1,640,256.07		NC8	2,644,878.56	1,655,055.31			
NC4	2,626,365.49	1,613,110.61		NC9	2,641,234.95	1,650,354.84			
NC5	2,627,562.38	1,619,578.73		NC10	2,643,980.06	1,655,531.75			
SURVEY LIMITS									
CORNER	NORTHING	EASTING	CORNER	NORTHING	EASTING				
SL1	2,628,340.46	1,612,745.15	SL6	2,637,780.48	1,640,988.24				
SL2	2,629,481.34	1,618,910.61	SL7	2,643,119.87	1,649,622.22				
SL3	2,641,596.07	1,639,894.63	SL8	2,645,754.53	1,654,590.82				
SL4	2,625,390.54	1,613,291.02	SL9	2,640,304.46	1,650,716.50				
SL5	2,626,615.08	1,619,908.55	SL10	2,643,104.09	1,655,996.24				
△ CONTROL COORDINATES △									
STATION	NORTHING	EASTING	ELEVATION	DESCRIPTION					
N END 1978	2,646,652.19	1,660,582.43	41.39	USACE SBC					
S END 1978	2,644,295.69	1,659,728.19	40.37	USACE SBC					
TERRA-9 2005	2,644,992.51	1,660,164.06	80.38	PORT OFFICE ANT. MOUNT					
PORT 1989	2,639,936.64	1,656,922.51	39.93	USACE SAC					
EQ-1	2,629,995.41	1,643,787.75	–	–					
VAN DUSEN GPS 1986	2,621,198.82	1,648,753.69	–	NGS SBC					
AWWU 1994	2,629,310.76	1,635,837.68	–	3" ALCAP					
NOAA/NOS TIDAL BENCH MARKS AT THE PORT OF ANCHORAGE 9455920									
TIDAL 16 1966	2,644,293	1,659,727	40.53	USCGS BENCH MARK SBC					
B 75 1964	2,644,598	1,660,095	36.82	USCGS BENCH MARK SBC					
NOAA/NOS TIDAL BENCH MARKS AT FIRE ISLAND 9455912									
BM 13 1974	2,620,685	1,605,138	28.41	NOS TIDAL BENCH MARK SBC					
RIFE 1960	2,620,520	1,604,180	29.99	USCGS TRI-STA SBC					

CONTRACT NO. W911KB-07-D-0005
CONTRACTOR TERRA SURVEYS, LLC
CITY PALMER STATE ALASKA

ALASKA DISTRICT
CORPS OF ENGINEERS
ANCHORAGE, ALASKA

SURVEYED: SC/SM/CM
DRAWN: S. LEATHAM
CHECKED: KDW
SUBMITTED:

ANCHORAGE, ALASKA
COOK INLET NAVIGATION CHANNEL
PROJECT CONDITION SURVEY
AUGUST 17–20, 2007

RECOMMENDED: PROJECT MANAGER
APPROVED: CHIEF OPERATIONS-READINESS BRANCH
DATE:

SURVEY NO. 2477-07
SCALE: 1" = 200'
SHEET 11 OF 11