

f Engineers ® ALASKA DISTRIC



NOTES

PRIMARY PROJECT HORIZONTAL CONTROL IS ALASKA STATE PLANE, ZONE 4, NAD83, IN US SURVEY FEET BASED ON A FULLY CONSTRAINED STATIC GPS NETWORK HOLDING THE PUBLISHED NAD83 (CORS) 2010.00 EPOCH VALUES OF NGS CORS STATIONS: "SOLDOTNA_AK2007 CORS ARP" (AC23 - PID DM7487), " DRIFTRIVERAK2006 CORS ARP" (AC17 - PID DM7481) AND "SEALROCKSAK2007 CORS ARP " (AC43 - PID

LOCAL PROJECT HORIZONTAL CONTROL IS ALASKA STATE PLANE, ZONE 4, NAD83, IN US SURVEY FEET HOLDING BRASS CAP SET IN ARMOR STONE "NINIL-2" AS N 2,215,653.51', E 1,336,081.03'.


- VERTICAL CONTROL IS MEAN LOWER LOW WATER (MLLW=0.0') U.S.SURVEY FEET, BASED ON THE NOAA/NOS TIDAL BENCH MARK LIST: "945 5653 NINILCHIK, ALASKA" PUBLISHED 07/14/2014. THIS TIDAL DATUM IS BASED ON THE 2007-2011 TIDAL EPOCH AND IS REFERENCED BY HOLDING NOAA/NOS TIDAL BENCH MARK "5653 F 2011" (PID BBCM32/VM#20900) AS 29.50' AND NOAA/NOS TIDAL BENCH MARK "945 5653 E" (VM#14160) AS
- VERTICAL TIES TO THE NATIONAL SPATIAL REFERENCE SYSTEM ARE BASED ON PUBLISHED NAVD88 (GEOID12A) ELEVATIONS HOLDING NOAA/USACE TIDAL BENCHMARK "5653 F 2011" (PID BBCM32/VM#20900)
- SOUNDINGS ARE IN U.S. SURVEY FEET AND ARE MINUS UNLESS OTHERWISE INDICATED.
- BATHYMETRY WAS COLLECTED APRIL 26, 2018. SOUNDINGS WERE COLLECTED USING AN R2SONIC 2022 MULTIBEAM ECHOSOUNDER OPERATING AT 400 KHZ. SOUND VELOCITY THOUGH THE WATER COLUMN WAS DETERMINED WITH AN AML BASE X SOUND VELOCITY PROBE. POSITION AND VESSEL ORIENTATION WERE MEASURED USING AN APPLANIX POSMV WAVE MASTER SYSTEM. RTK CORRECTIONS WERE BROADCAST FROM A LOCAL BASE STATION OCCUPYING "NINIL-2". DATA WAS COLLECTED AND PROCESSED USING HYPACK 2018 SOFTWARE. HORIZONTAL CONTROL WAS SURVEYED USING RTK GNSS EQUIPMENT AND TECHNIQUES. VERTICAL CONTROL WAS SURVEYED USING DIFFERENTIAL LEVELING TECHNIQUES. TIDE ELEVATIONS WERE MEASURED USING A TRIMBLE R10 RTK SYSTEM.
- THIS DRAWING INDICATES GENERAL CONDITIONS AT THE TIME OF THE SURVEY.
- MAP SOUNDINGS ARE BINNED AT 15 FEET AND ARE SHOAL-BIASED. CONTOURS ARE BASED ON 3 FEET BINNED SHOAL-BIASED SOUNDINGS. VOLUME SOUNDINGS ARE BINNED AT 3 FEET AND ARE MEAN VALUE

ļ	SURVEY CONTROL DATA						
í	STATION	NORTHING	EASTING	MLLW	DESCRIPTION		
ı	9455653 E	2,215,592.06	1,336,145.04	30.62	METAL ROD IN BW ROCK		
ı	9455653 F	2,214,548.53	1,335,413.68	29.50	METAL ROD IN GROUND		
ı	9455653 G	2,214,391.31	1,335,295.69	29.78	METAL ROD IN GROUND		
Z	DL	2,215,518.12	1,336,349.90	25.38	ALUMINUM CAP		
	NINIL-2	2,215,653.51	1,336,081.03	29.53	USACE SBC		

PRC	DJECT LIN	/ITS	PRC	DJECT LIN	1ITS
ORNER#	NORTHING	EASTING	CORNER#	NORTHING	EASTI
1	2,215,380.30	1,336,164.37	8	2,215,407.15	1,336,26
2	2,215,425.79	1,336,111.41	9	2,215,588.16	1,336,26
3	2,215,123.35	1,335,851.63	10	2,216,017.64	1,335,81
4	2,215,058.05	1,335,927.64	11	2,215,980.40	1,335,78
5	2,215,045.59	1,335,954.77	12	2,215,551.92	1,336,23
6	2,215,074.98	1,335,968.27	13	2,215,442.00	1,336,23
7	2,215,347.60	1,336,202.44			


		NAVIGA	TION AIDS
USCG NO.	NORTHING	EASTING	DESCRIPTION
26255	2,215,714	1,336,165	CHANNEL ENTRANCE LIGHT
26260	2,215,636	1,336,257	ROCK SILL NORTH DAYBEACON
26265	2,215,696	1,336,042	ROCK SILL SOUTH DAYBEACON

VOLUME COMPUTATIONS					
AREA A: BASIN	MLLW=0	CU. YD.			
AVAILABLE TO PROJECT DEPTH (PD)	+3.3	4,954			
AVAILABLE TO MAX PAY DEPTH (MP)	+2.3	6,729			
AVAILABLE SIDE SLOPES (SS) AT 3:1 (H:V) & 25' WIDE	VARIES	1,601			
AREA B: ENTRANCE CHANNEL					
AVAILABLE TO PROJECT DEPTH	+9.3	1,014			
AVAILABLE TO MAX PAY DEPTH (MP)	+8.3	2,192			
AVAILABLE SIDE SLOPES (SS) AT 3:1 (H:V) & 25' WIDE	VAIRES	3,472			
TOTAL MAXIMUM VOLUME AVAILABLE (MP)		13,994			



THIS HYDROGRAPHIC SURVEY WAS COMPLETED UNDER THE OVERSIGHT OF AN ACSM/THOSOA CERTIFIED HYDROGRAPHER CORY S. HUGHES C.H. (245)

IDENTIFICATION 2-NIN-92-07-51





US Army Corps of Engineers ® ALAŠKA DISTRICT



NOTES

PRIMARY PROJECT HORIZONTAL CONTROL IS ALASKA STATE PLANE, ZONE 4, NAD83, IN US SURVEY FEET BASED ON A FULLY CONSTRAINED STATIC GPS NETWORK HOLDING THE PUBLISHED NAD83 (CORS) 2010.00 EPOCH VALUES OF NGS CORS STATIONS: "SOLDOTNA_AK2007 CORS ARP" (AC23 - PID DM7487), " DRIFTRIVERAK2006 CORS ARP" (AC17 - PID DM7481) AND "SEALROCKSAK2007 CORS ARP " (AC43 - PID

LOCAL PROJECT HORIZONTAL CONTROL IS ALASKA STATE PLANE, ZONE 4, NAD83, IN US SURVEY FEET HOLDING BRASS CAP SET IN ARMOR STONE "NINIL-2" AS N 2,215,653.51', E 1,336,081.03'.

VERTICAL CONTROL IS MEAN LOWER LOW WATER (MLLW=0.0') U.S.SURVEY FEET, BASED ON THE NOAA/NOS TIDAL BENCH MARK LIST: "945 5653 NINILCHIK, ALASKA" PUBLISHED 07/14/2014. THIS TIDAL DATUM IS BASED ON THE 2007-2011 TIDAL EPOCH AND IS REFERENCED BY HOLDING NOAA/NOS TIDAL BENCH MARK "5653 F 2011" (PID BBCM32/VM#20900) AS 29.50' AND NOAA/NOS TIDAL BENCH MARK "945 5653 E" (VM#14160) AS

VERTICAL TIES TO THE NATIONAL SPATIAL REFERENCE SYSTEM ARE BASED ON PUBLISHED NAVD88 (GEOID12A) ELEVATIONS HOLDING NOAA/USACE TIDAL BENCHMARK "5653 F 2011" (PID BBCM32/VM#20900)

SOUNDINGS ARE IN U.S. SURVEY FEET AND ARE MINUS UNLESS OTHERWISE INDICATED.

BATHYMETRY WAS COLLECTED APRIL 26, 2018. SOUNDINGS WERE COLLECTED USING AN R2SONIC 2022 MULTIBEAM ECHOSOUNDER OPERATING AT 400 KHZ. SOUND VELOCITY THOUGH THE WATER COLUMN WAS DETERMINED WITH AN AML BASE X SOUND VELOCITY PROBE. POSITION AND VESSEL ORIENTATION WERE MEASURED USING AN APPLANIX POSMV WAVE MASTER SYSTEM. RTK CORRECTIONS WERE BROADCAST FROM A LOCAL BASE STATION OCCUPYING "NINIL-2". DATA WAS COLLECTED AND PROCESSED USING HYPACK 2018 SOFTWARE. HORIZONTAL CONTROL WAS SURVEYED USING RTK GNSS EQUIPMENT AND TECHNIQUES. VERTICAL CONTROL WAS SURVEYED USING DIFFERENTIAL LEVELING TECHNIQUES. TIDE ELEVATIONS WERE MEASURED USING A TRIMBLE R10 RTK SYSTEM.

. THIS DRAWING INDICATES GENERAL CONDITIONS AT THE TIME OF THE SURVEY.

MAP SOUNDINGS ARE BINNED AT 15 FEET AND ARE SHOAL-BIASED. CONTOURS ARE BASED ON 3 FEET BINNED SHOAL-BIASED SOUNDINGS. VOLUME SOUNDINGS ARE BINNED AT 3 FEET AND ARE MEAN VALUE


1	SURVEY CONTROL DATA						
Į.	STATION	NORTHING	EASTING	MLLW	DESCRIPTION		
N.	9455653 E	2,215,592.06	1,336,145.04	30.62	METAL ROD IN BW ROCK		
r	9455653 F	2,214,548.53	1,335,413.68	29.50	METAL ROD IN GROUND		
g,	9455653 G	2,214,391.31	1,335,295.69	29.78	METAL ROD IN GROUND		
A	DL	2,215,518.12	1,336,349.90	25.38	ALUMINUM CAP		
	NINIL-2	2,215,653.51	1,336,081.03	29.53	USACE SBC		

PROJECT LIMITS					
CORNER#	NORTHING	EASTING			
1	2,215,380.30	1,336,164.37			
2	2,215,425.79	1,336,111.41			
3	2,215,123.35	1,335,851.63			
4	2,215,058.05	1,335,927.64			
5	2,215,045.59	1,335,954.77			
6	2,215,074.98	1,335,968.27			
7	2,215,347.60	1,336,202.44			

CORNER#	NORTHING	EASTING	
8	2,215,407.15	1,336,268.37	
9	2,215,588.16	1,336,268.15	
10	2,216,017.64	1,335,816.29	
11	2,215,980.40	1,335,782.90	
12	2,215,551.92	1,336,233.70	
13	2,215,442.00	1,336,232.41	

NAVIGATION AIDS					
USCG NO.	NORTHING	EASTING	DESCRIPTION		
26255	2,215,714	1,336,165	CHANNEL ENTRANCE LIGHT		
26260	2,215,636	1,336,257	ROCK SILL NORTH DAYBEACON		
26265	2,215,696	1,336,042	ROCK SILL SOUTH DAYBEACON		

VOLUME COMPUTATIONS						
AREA A: BASIN	MLLW=0	CU. YD.				
AVAILABLE TO PROJECT DEPTH (PD)	+3.3	4,954				
AVAILABLE TO MAX PAY DEPTH (MP)	+2.3	6,729				
AVAILABLE SIDE SLOPES (SS) AT 3:1 (H:V) & 25' WIDE	VARIES	1,601				
AREA B: ENTRANCE CHANNEL						
AVAILABLE TO PROJECT DEPTH	+9.3	1,014				
AVAILABLE TO MAX PAY DEPTH (MP)	+8.3	2,192				
AVAILABLE SIDE SLOPES (SS) AT 3:1 (H:V) & 25' WIDE	VAIRES	3,472				
TOTAL MAXIMUM VOLUME AVAILABLE (MP)		13,994				



THIS HYDROGRAPHIC SURVEY WAS COMPLETED UNDER THE OVERSIGHT OF AN ACSM/THOSOA CERTIFIED HYDROGRAPHER CORY S. HUGHES C.H. (245)

IDENTIFICATION 2-NIN-92-07-51