



NOTES

. PRIMARY PROJECT HORIZONTAL CONTROL IS ALASKA STATE PLANE, ZONE 1, NAD83 2011 (2010.00), IN US SURVEY FEET BASED ON A FULLY CONSTRAINED STATIC GPS NETWORK HOLDING THE PUBLISHED NAD83 2011 EPOCH 2010.00 VALUES OF NGS CORS STATIONS:"LEVEL ISLAND 5 CORS ARP" (PID DJ3033); "BIORKA ISLAND 6 CORS ARP" (PID DK6554); "PORTALEXANDERAK2005 CORS ARP" (PID DL6695).

LOCAL PROJECT HORIZONTAL CONTROL IS ALASKA STATE PLANE, ZONE 1, NAD83 2011 (2010.00), IN US SURVEY FEET HOLDING "1600 P 1998" AS N 1,908,750.35' E 2,352,961.21', AND "WC-3 2001" AS N 1,912,051.12' E


- 2. VERTICAL CONTROL IS MEAN LOWER LOW WATER (MLLW=0.0'), BASED ON THE NOAA/NOS TIDAL BENCH MARK LIST "9451600 SITKA, BARANOF ISLAND, SITKA SOUND ALASKA", PUBLISHED 10/06/2011. THIS TIDAL DATUM IS BASED ON THE 1983-2001 TIDAL EPOCH AND IS REFERENCED BY HOLDING NOAA/NOS TIDAL BENCH MARK "945 1600 L 1982" (VM#1186) AS 40.32'.
- 3. VERTICAL TIES TO THE NATIONAL SPATIAL REFERENCE SYSTEM ARE BASED ON PUBLISHED NAVD88 (GEOID 12B) ELEVATIONS HOLDING NOAA/USACE TIDAL BENCHMARK "1600 P 1998" (PID BBFF16/VM#14007) AS 22.37'.
- 4. SOUNDINGS ARE IN US SURVEY FEET AND ARE MINUS UNLESS OTHERWISE INDICATED.
- 5. BATHYMETRY WAS COLLECTED MARCH 25 28, 2016. SOUNDINGS WERE COLLECTED USING AN R2SONIC 2022 MULTIBEAM ECHOSOUNDER OPERATING AT 200 KHZ. SOUND VELOCITY THROUGH THE WATER COLUMN WAS DETERMINED WITH AN AML BASE X SOUND VELOCITY PROBE. POSITIONING AND VESSEL ORIENTATION WERE MEASURED USING AN APPLANIX POS OCEANMASTER V5 SYSTEM. DATA WAS COLLECTED AND PROCESSED USING QINSY 8.1 SOFTWARE. HORIZONTAL CONTROL WAS SURVEYED USING RTK GNSS EQUIPMENT AND TECHNIQUES. VERTICAL CONTROL WAS SURVEYED USING DIFFERENTIAL LEVELING
- 6. THIS DRAWING INDICATES GENERAL CONDITIONS AT THE TIME OF THE SURVEY.
- . MAP SOUNDINGS ARE BINNED AT 24 FEET AND ARE SHOAL BIASED. CONTOURS ARE BASED ON 12 FEET BINNED SHOAL-BIASED SOUNDINGS. VOLUME SOUNDINGS ARE BINNED AT 3 FEET AND ARE MEAN VALUE.

SURVEY CONTROL DATA						
STATION NORTHING EASTING MLLW DESCRIPTION						
1600 P 1998	1,908,750.35	2,352,961.21	22.83	3.5" DOMED NOS BC		
CH-9 2016	1,909,495.16	2,354,480.57	19.62	3.5" DOMED USACE BC		
LB-2 1978	1,908,780.34	2,354,476.60	14.61	3.5" DOMED NOS BC		
WC-3 2001	1,912,051.12	2,350,575.56	16.76	3.25" DOMED SBC		
WC-4-2001	1,910,740.83	2,350,128.42	9.37	3.25" DOMED SBC		

Q ₄	NAVIGATION AIDS						
	USCG NO.	NORTHING	EASTING	DESCRIPTION			
	25030	1,910,583	2,350,925	SITKA HARBOR CHANNEL LIGHT 9			
	25035	1,910,465	2,351,204	HARBOR ROCK DAYBEACON			
	25040	1,910,270	2,351,236	SITKA HARBOR LIGHT 11			
	25043	1,909,262	2,351,607	SITKA HARBOR GOVERNMENT PIER NORTH LIGHT			
	25045	1,909,052	2,351,807	SITKA HARBOR GOVERNMENT PIER SOUTH LIGHT			

PROJECT LIMITS			PRC	DJECT LIN	MITS
CORNER#	NORTHING	EASTING	CORNER#	NORTHING	EASTING
1	1,911,072.93	2,350,754.82	5	1,910,572.24	2,351,419.57
2	1,910,943.90	2,350,678.32	6	1,910,491.12	2,351,289.02
3	1,910,828.01	2,351,167.87	7	1,910,087.31	2,351,589.05
4	1,910,708.91	2,351,074.63	8	1,910,037.82	2,351,447.45


V.							
	VOLUME COMPUTATIONS						
30	AREA A: CHANNEL	MLLW=0	CU. YD.				
33	AVAILABLE TO PROJECT DEPTH (PD)	-22.0	6				
81	AVAILABLE TO MAX PAY DEPTH (MP)	-23.0	149				
	AVAILABLE SIDE SLOPES (SS) AT 3:1 (H:V) & 25 FT WIDE	VARIES	1				
	TOTAL MAXIMUM VOLUME AVAILABLE (MP + SS)		150				



THIS HYDROGRAPHIC SURVEY WAS COMPLETED UNDER THE OVERSIGHT OF AN ACSM/THSOA CERTIFIED HYDROGRAPHER



SHEET IDENTIFICATION 1-SIT-92-07-15





of Engineers ®



NOTES

PRIMARY PROJECT HORIZONTAL CONTROL IS ALASKA STATE PLANE, ZONE 1, NAD83 2011 (2010.00), IN US SURVEY FEET BASED ON A FULLY CONSTRAINED STATIC GPS NETWORK HOLDING THE PUBLISHED NAD83 2011 EPOCH 2010.00 VALUES OF NGS CORS STATIONS:"LEVEL ISLAND 5 CORS ARP" (PID DJ3033); "BIORKA ISLAND 6 CORS ARP" (PID DK6554); "PORTALEXANDERAK2005 CORS ARP" (PID DL6695).

LOCAL PROJECT HORIZONTAL CONTROL IS ALASKA STATE PLANE, ZONE 1, NAD83 2011 (2010.00), IN US SURVEY FEET HOLDING "1600 P 1998" AS N 1,908,750.35' E 2,352,961.21', AND "WC-3 2001" AS N 1,912,051.12' E

- 2. VERTICAL CONTROL IS MEAN LOWER LOW WATER (MLLW=0.0'), BASED ON THE NOAA/NOS TIDAL BENCH MARK LIST "9451600 SITKA, BARANOF ISLAND, SITKA SOUND ALASKA", PUBLISHED 10/06/2011. THIS TIDAL MARK "945 1600 L 1982" (VM#1186) AS 40.32'.
- 3. VERTICAL TIES TO THE NATIONAL SPATIAL REFERENCE SYSTEM ARE BASED ON PUBLISHED NAVD88 (GEOID 12B) ELEVATIONS HOLDING NOAA/USACE TIDAL BENCHMARK "1600 P 1998" (PID BBFF16/VM#14007) AS 22.37'.
- 4. SOUNDINGS ARE IN US SURVEY FEET AND ARE MINUS UNLESS OTHERWISE INDICATED.
- 5. BATHYMETRY WAS COLLECTED MARCH 25 28, 2016. SOUNDINGS WERE COLLECTED USING AN R2SONIC WAS DETERMINED WITH AN AML BASE X SOUND VELOCITY PROBE. POSITIONING AND VESSEL ORIENTATION WERE MEASURED USING AN APPLANIX POS OCEANMASTER V5 SYSTEM. DATA WAS COLLECTED AND PROCESSED USING QINSY 8.1 SOFTWARE. HORIZONTAL CONTROL WAS SURVEYED USING RTK GNSS EQUIPMENT AND TECHNIQUES. VERTICAL CONTROL WAS SURVEYED USING DIFFERENTIAL LEVELING
- 6. THIS DRAWING INDICATES GENERAL CONDITIONS AT THE TIME OF THE SURVEY.
- . MAP SOUNDINGS ARE BINNED AT 24 FEET AND ARE SHOAL BIASED. CONTOURS ARE BASED ON 12 FEET BINNED SHOAL-BIASED SOUNDINGS. VOLUME SOUNDINGS ARE BINNED AT 3 FEET AND ARE MEAN VALUE.

	SURVEY CONTROL DATA						
STATION NORTHING EASTING MLLW DESCRIPTION							
	1600 P 1998	1,908,750.35	2,352,961.21	22.83	3.5" DOMED NOS BC		
	CH-9 2016	1,909,495.16	2,354,480.57	19.62	3.5" DOMED USACE BC		
	LB-2 1978	1,908,780.34	2,354,476.60	14.61	3.5" DOMED NOS BC		
	WC-3 2001	1,912,051.12	2,350,575.56	16.76	3.25" DOMED SBC		
	WC-4-2001	1,910,740.83	2,350,128.42	9.37	3.25" DOMED SBC		

NAVIGATION AIDS						
USCG NO.	NORTHING	EASTING	DESCRIPTION			
25030	1,910,583 2,350,925		SITKA HARBOR CHANNEL LIGHT 9			
25035	1,910,465	2,351,204	HARBOR ROCK DAYBEACON			
25040	1,910,270	2,351,236	SITKA HARBOR LIGHT 11			
25043	1,909,262	2,351,607	SITKA HARBOR GOVERNMENT PIER NORTH LIGHT			
25045	1,909,052	2,351,807	SITKA HARBOR GOVERNMENT PIER SOUTH LIGHT			

PROJECT LIMITS			PROJECT LIMITS		
CORNER#	NORTHING	EASTING	CORNER#	NORTHING	EASTING
1	1,911,072.93	2,350,754.82	5	1,910,572.24	2,351,419.57
2	1,910,943.90	2,350,678.32	6	1,910,491.12	2,351,289.02
3	1,910,828.01	2,351,167.87	7	1,910,087.31	2,351,589.05
4	1,910,708.91	2,351,074.63	8	1,910,037.82	2,351,447.45

VOLUME COMPUTATIONS						
AREA A: CHANNEL	MLLW=0	CU. YD.				
AVAILABLE TO PROJECT DEPTH (PD)	-22.0	6				
AVAILABLE TO MAX PAY DEPTH (MP)	-23.0	149				
AVAILABLE SIDE SLOPES (SS) AT 3:1 (H:V) & 25 FT WIDE	VARIES	1				
TOTAL MAXIMUM VOLUME AVAILABLE (MP + SS)		150				




THIS HYDROGRAPHIC SURVEY WAS COMPLETED UNDER THE OVERSIGHT OF AN ACSM/THSOA CERTIFIED HYDROGRAPHER


David R. Neff C.H. (275)

IDENTIFICATION 1-SIT-92-07-15

Sheet 2 of 4

SITKA, ALASKA WESTERN CHANNEL PROJECT CONDITION SURVE 03/18-29/2016







NOTES

. PRIMARY PROJECT HORIZONTAL CONTROL IS ALASKA STATE PLANE, ZONE 1, NAD83 2011 (2010.00), IN US SURVEY FEET BASED ON A FULLY CONSTRAINED STATIC GPS NETWORK HOLDING THE PUBLISHED NAD83 2011 EPOCH 2010.00 VALUES OF NGS CORS STATIONS:"LEVEL ISLAND 5 CORS ARP" (PID DJ3033); "BIORKA ISLAND 6 CORS ARP" (PID DK6554); "PORTALEXANDERAK2005 CORS ARP" (PID DL6695).

LOCAL PROJECT HORIZONTAL CONTROL IS ALASKA STATE PLANE, ZONE 1, NAD83 2011 (2010.00), IN US SURVEY FEET HOLDING "1600 P 1998" AS N 1,908,750.35' E 2,352,961.21', AND "WC-3 2001" AS N 1,912,051.12' E

- 2. VERTICAL CONTROL IS MEAN LOWER LOW WATER (MLLW=0.0'), BASED ON THE NOAA/NOS TIDAL BENCH MARK LIST "9451600 SITKA, BARANOF ISLAND, SITKA SOUND ALASKA", PUBLISHED 10/06/2011. THIS TIDAL DATUM IS BASED ON THE 1983-2001 TIDAL EPOCH AND IS REFERENCED BY HOLDING NOAA/NOS TIDAL BENCH MARK "945 1600 L 1982" (VM#1186) AS 40.32'.
- 3. VERTICAL TIES TO THE NATIONAL SPATIAL REFERENCE SYSTEM ARE BASED ON PUBLISHED NAVD88 (GEOID 12B) ELEVATIONS HOLDING NOAA/USACE TIDAL BENCHMARK "1600 P 1998" (PID BBFF16/VM#14007) AS 22.37'.
- 5. BATHYMETRY WAS COLLECTED MARCH 25 28, 2016. SOUNDINGS WERE COLLECTED USING AN R2SONIC 2022 MULTIBEAM ECHOSOUNDER OPERATING AT 200 KHZ. SOUND VELOCITY THROUGH THE WATER COLUMN WAS DETERMINED WITH AN AML BASE X SOUND VELOCITY PROBE. POSITIONING AND VESSEL ORIENTATION WERE MEASURED USING AN APPLANIX POS OCEANMASTER V5 SYSTEM. DATA WAS COLLECTED AND
- 6. THIS DRAWING INDICATES GENERAL CONDITIONS AT THE TIME OF THE SURVEY.
- . MAP SOUNDINGS ARE BINNED AT 24 FEET AND ARE SHOAL BIASED. CONTOURS ARE BASED ON 12 FEET BINNED SHOAL-BIASED SOUNDINGS. VOLUME SOUNDINGS ARE BINNED AT 3 FEET AND ARE MEAN VALUE.

	SURVEY CONTROL DATA						
STATION NORTHING EASTING MLLW DESCRIPTION							
	1600 P 1998	1,908,750.35	2,352,961.21	22.83	3.5" DOMED NOS BC		
	CH-9 2016	1,909,495.16	2,354,480.57	19.62	3.5" DOMED USACE BC		
	LB-2 1978	1,908,780.34	2,354,476.60	14.61	3.5" DOMED NOS BC		
	WC-3 2001	1,912,051.12	2,350,575.56	16.76	3.25" DOMED SBC		
	WC-4-2001	1,910,740.83	2,350,128.42	9.37	3.25" DOMED SBC		

NAVIGATION AIDS						
USCG NO. NORTHING EASTING			DESCRIPTION			
25030	25030 1,910,583 2,350,925		SITKA HARBOR CHANNEL LIGHT 9			
25035 1,910,465 2,351,20		2,351,204	HARBOR ROCK DAYBEACON			
25040	1,910,270	2,351,236	SITKA HARBOR LIGHT 11			
25043	1,909,262	2,351,607	SITKA HARBOR GOVERNMENT PIER NORTH LIGHT			
25045	1,909,052	2,351,807	SITKA HARBOR GOVERNMENT PIER SOUTH LIGHT			


PROJECT LIMITS			PROJECT LIMITS			PRC	DJECT LIN	MITS
CORNER#	NORTHING	EASTING	CORNER#	NORTHING	EASTING			
1	1,911,072.93	2,350,754.82	5	1,910,572.24	2,351,419.57			
2	1,910,943.90	2,350,678.32	6	1,910,491.12	2,351,289.02			
3	1,910,828.01	2,351,167.87	7	1,910,087.31	2,351,589.05			
4	1,910,708.91	2,351,074.63	8	1,910,037.82	2,351,447.45			


10							
VOLUME COMPUTATIONS							
30	AREA A: CHANNEL	MLLW=0	CU. YD.				
30	AVAILABLE TO PROJECT DEPTH (PD)	-22.0	6				
KV.	AVAILABLE TO MAX PAY DEPTH (MP)	-23.0	149				
B	AVAILABLE SIDE SLOPES (SS) AT 3:1 (H:V) & 25 FT WIDE	VARIES	1				
	TOTAL MAXIMUM VOLUME AVAILABLE (MP + SS)		150				




THIS HYDROGRAPHIC SURVEY WAS COMPLETED UNDER THE OVERSIGHT OF AN ACSM/THSOA CERTIFIED HYDROGRAPHER











NOTES

PRIMARY PROJECT HORIZONTAL CONTROL IS ALASKA STATE PLANE, ZONE 1, NAD83 2011 (2010.00), IN US SURVEY FEET BASED ON A FULLY CONSTRAINED STATIC GPS NETWORK HOLDING THE PUBLISHED NAD83 2011 EPOCH 2010.00 VALUES OF NGS CORS STATIONS:"LEVEL ISLAND 5 CORS ARP" (PID DJ3033); "BIORKA ISLAND 6 CORS ARP" (PID DK6554); "PORTALEXANDERAK2005 CORS ARP" (PID DL6695).

LOCAL PROJECT HORIZONTAL CONTROL IS ALASKA STATE PLANE, ZONE 1, NAD83 2011 (2010.00), IN US SURVEY FEET HOLDING "1600 P 1998" AS N 1,908,750.35' E 2,352,961.21', AND "WC-3 2001" AS N 1,912,051.12' E

- 2. VERTICAL CONTROL IS MEAN LOWER LOW WATER (MLLW=0.0'), BASED ON THE NOAA/NOS TIDAL BENCH MARK LIST "9451600 SITKA, BARANOF ISLAND, SITKA SOUND ALASKA", PUBLISHED 10/06/2011. THIS TIDAL DATUM IS BASED ON THE 1983-2001 TIDAL EPOCH AND IS REFERENCED BY HOLDING NOAA/NOS TIDAL BENCH MARK "945 1600 L 1982" (VM#1186) AS 40.32'.
- 3. VERTICAL TIES TO THE NATIONAL SPATIAL REFERENCE SYSTEM ARE BASED ON PUBLISHED NAVD88 (GEOID 12B) ELEVATIONS HOLDING NOAA/USACE TIDAL BENCHMARK "1600 P 1998" (PID BBFF16/VM#14007) AS 22.37'.
- 4. SOUNDINGS ARE IN US SURVEY FEET AND ARE MINUS UNLESS OTHERWISE INDICATED.
- 5. BATHYMETRY WAS COLLECTED MARCH 25 28, 2016. SOUNDINGS WERE COLLECTED USING AN R2SONIC 2022 MULTIBEAM ECHOSOUNDER OPERATING AT 200 KHZ. SOUND VELOCITY THROUGH THE WATER COLUMN WAS DETERMINED WITH AN AML BASE X SOUND VELOCITY PROBE. POSITIONING AND VESSEL ORIENTATION WERE MEASURED USING AN APPLANIX POS OCEANMASTER V5 SYSTEM. DATA WAS COLLECTED AND PROCESSED USING QINSY 8.1 SOFTWARE. HORIZONTAL CONTROL WAS SURVEYED USING RTK GNSS EQUIPMENT AND TECHNIQUES. VERTICAL CONTROL WAS SURVEYED USING DIFFERENTIAL LEVELING
- 6. THIS DRAWING INDICATES GENERAL CONDITIONS AT THE TIME OF THE SURVEY.
- . MAP SOUNDINGS ARE BINNED AT 24 FEET AND ARE SHOAL BIASED. CONTOURS ARE BASED ON 12 FEET BINNED SHOAL-BIASED SOUNDINGS. VOLUME SOUNDINGS ARE BINNED AT 3 FEET AND ARE MEAN VALUE.

SURVEY CONTROL DATA							
	STATION	NORTHING	EASTING	MLLW	DESCRIPTION		
	1600 P 1998	1,908,750.35	2,352,961.21	22.83	3.5" DOMED NOS BC		
	CH-9 2016	1,909,495.16	2,354,480.57	19.62	3.5" DOMED USACE BC		
	LB-2 1978	1,908,780.34	2,354,476.60	14.61	3.5" DOMED NOS BC		
	WC-3 2001	1,912,051.12	2,350,575.56	16.76	3.25" DOMED SBC		
	WC-4-2001	1,910,740.83	2,350,128.42	9.37	3.25" DOMED SBC		

NAVIGATION AIDS				
USCG NO.	NORTHING	EASTING	DESCRIPTION	
25030	1,910,583	2,350,925	SITKA HARBOR CHANNEL LIGHT 9	
25035	1,910,465	2,351,204	HARBOR ROCK DAYBEACON	
25040	1,910,270	2,351,236	SITKA HARBOR LIGHT 11	
25043	1,909,262	2,351,607	SITKA HARBOR GOVERNMENT PIER NORTH LIGHT	
25045	1,909,052	2,351,807	SITKA HARBOR GOVERNMENT PIER SOUTH LIGHT	

PROJECT LIMITS				PROJECT LIMITS		
CORNER#	NORTHING	EASTING		CORNER#	NORTHING	EASTING
1	1,911,072.93	2,350,754.82		5	1,910,572.24	2,351,419.57
2	1,910,943.90	2,350,678.32		6	1,910,491.12	2,351,289.02
3	1,910,828.01	2,351,167.87		7	1,910,087.31	2,351,589.05
4	1,910,708.91	2,351,074.63		8	1,910,037.82	2,351,447.45

VOLUME COMPUTATIONS					
AREA A: CHANNEL	MLLW=0	CU. YD.			
AVAILABLE TO PROJECT DEPTH (PD)	-22.0	6			
AVAILABLE TO MAX PAY DEPTH (MP)	-23.0	149			
AVAILABLE SIDE SLOPES (SS) AT 3:1 (H:V) & 25 FT WIDE	VARIES	1			
TOTAL MAXIMUM VOLUME AVAILABLE (MP + SS)		150			



THIS HYDROGRAPHIC SURVEY WAS COMPLETED UNDER THE OVERSIGHT OF AN ACSM/THSOA CERTIFIED HYDROGRAPHER

David R. Neff C.H. (275)

IDENTIFICATION 1-SIT-92-07-15

Sheet 4 of 4